



Finess Dubbeldek mat (High opacity wall paint) [UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 27-7-2016 Revision date: 27-7-2016 Supersedes: 10-7-2013 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Finess Dubbeldek mat (High opacity wall paint)
[UNOFFICIAL DOCUMENT]
Product code : 45042060101
Product group : Wallpaint.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer uses, Professional use, Industrial use
Use of the substance/mixture : Industrial and decoration painting

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

S.P.S. BV
Zilverenberg 16
5234 GM 's-Hertogenbosch. - Nederland.
T +31 (0)73 642 27 10 - F +31 (0)73 642 60 95
info@spsbv.com - www.spsbv.com

Responsible formatting SDS

Mantech Nederland B.V.
Kobaltweg 7
5234 GN 's-Hertogenbosch - Nederland
T +31 (0)73 70 70 112 - F +31 (0)73 64 43 861
info@mantechbv.nl - www.mantechbv.nl

1.4. Emergency telephone number

Emergency number : SPS BV.: +31 73 642 27 10 [7:30 - 16:30]

NL - Nationaal Vergiftigingen Informatie Centrum (NVIC)
Emergency telephone (24 hours): +31 30 274 88 88
(Only for doctors to inform accidental poisoning)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : Not applicable
Hazard statements (CLP) : Not applicable
Precautionary statements (CLP) : P102 - Keep out of reach of children
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, protective clothing, eye protection
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
[Spray application; P261 - Avoid breathing spay.]
EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one(2634-33-5)(220-120-9). May produce an allergic reaction
EUH210 - Safety data sheet available on request
Security closing plug for children : Not applicable
Tactile warning : Not applicable

Finess Dubbeldek mat (High opacity wall paint)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc substance with national workplace exposure limit(s) (NL)	(CAS No) 14807-96-6 (EC no) 238-877-9	2,5 - 10	Not classified
1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one	(CAS No) 2634-33-5 (EC no) 220-120-9 (EC index no) 613-088-00-6	0,005=< C < 0,05	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400

Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one	(CAS No) 2634-33-5 (EC no) 220-120-9 (EC index no) 613-088-00-6	(C >= 0,05) Skin Sens. 1, H317

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
First-aid measures after inhalation	: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.
First-aid measures after skin contact	: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
First-aid measures after eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
First-aid measures after ingestion	: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : No information is on file to date regarding acute and/or delayed post-exposure symptoms and effects.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

5.3. Advice for firefighters

Precautionary measures fire	: Cool closed containers exposed to fire with water.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses.

Finess Dubbeldek mat (High opacity wall paint)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Use personal protective equipment as required.
Emergency procedures : Do not smoke. Ventilate area. Do not breathe vapours.

6.1.2. For emergency responders

- Protective equipment : Equip rescue crew with proper protection.
Emergency procedures : No smoking. Ventilate area. Do not breathe vapours.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
Other information : Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep container tightly closed. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. For personal protection see Section 8. Comply with the health and safety at work laws.
Hygiene measures : Smoking, eating and drinking should be prohibited in application area.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in accordance with local/national regulations.
Storage temperature : 5 - 30 °C Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight
Prohibitions on mixed storage : Store separately from oxidising agents and strongly alkaline and strongly acidic materials.
Storage area : Prevent unauthorised access.
Special rules on packaging : Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment:

Protective goggles. Gloves. In case of inadequate ventilation wear respiratory protection.

Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged contact, use rubber or neoprene gloves. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred

Eye protection:

Finess Dubbeldek mat (High opacity wall paint)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Use safety eyewear designed to protect against splash of liquids

Skin and body protection:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Every part of the skin which had contact with the product should have been washed thoroughly

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Different colours.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: 8 - 9 @ 20 °C
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: 0 °C Water
Boiling point	: 100 °C Water
Flash point	: Not applicable
Auto-ignition temperature	: The product does not ignites spontaneously.
Decomposition temperature	: When exposed to heat, may decompose liberating hazardous gases
Flammability (solid, gas)	: The product is not flammable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1525 - 1575 kg/m ³
Solubility	: Miscible with water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 5 - 5,5 Pa.s @ 20 °C [LC 3]
Explosive properties	: No dangerous reactions known.
Oxidising properties	: No data available.
Explosive limits	: No data available

9.2. Other information

VOC content : (cat.A/a): 30 g/l (2010). This product contains max. 5 g/l VOC.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

See Heading 7.

Finess Dubbeldek mat (High opacity wall paint)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

10.6. Hazardous decomposition products

Such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: There are no data available on the preparation itself (This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]. This product is not hazardous but contains hazardous components)
Skin corrosion/irritation	: Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin pH: 8 - 9 @ 20 °C
Serious eye damage/irritation	: The liquid splashed in the eyes may cause irritation and reversible damage pH: 8 - 9 @ 20 °C
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The mixture has been assessed following the conventional method of the Regulation (EC) No. 1272/2008 [CLP] and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See Heading 3.

1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one (2634-33-5)	
LC50 fish 1	1,6 mg/l [Oncorhynchus mykiss, 96h]
EC50 Daphnia 1	4,8 mg/l
ErC50 (algae)	0,11 mg/l [Selenastrum capricornutum, 72h]

12.2. Persistence and degradability

Finess Dubbeldek mat (High opacity wall paint) [UNOFFICIAL DOCUMENT]	
Persistence and degradability	There are no data available on the preparation itself.

12.3. Bioaccumulative potential

Finess Dubbeldek mat (High opacity wall paint) [UNOFFICIAL DOCUMENT]	
Log Pow	No data available
Bioaccumulative potential	There are no data available on the preparation itself.

1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one (2634-33-5)	
BCF fish 1	6,95 (OECD 305)
Log Kow	0,7 (OECD 117)

12.4. Mobility in soil

Finess Dubbeldek mat (High opacity wall paint) [UNOFFICIAL DOCUMENT]	
Ecology - soil	There are no data available on the preparation itself.

12.5. Results of PBT and vPvB assessment

Finess Dubbeldek mat (High opacity wall paint) [UNOFFICIAL DOCUMENT]	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

Finess Dubbeldek mat (High opacity wall paint)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

12.6. Other adverse effects

Additional information : Product may not flow into sewer or superficial water

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Do not allow to enter drains or water courses.
Waste disposal recommendations : Dispose of this material and its container to hazardous or special waste collection point.
Additional information : Uncleaned packaging: Recommendation: Not completely empty packaging must be treated complying Directive 91/689/EEC.
European List of Waste (LoW) code : 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Special transport precautions : Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

IBC code : Not determined.
Ship type : Not determined.
Pollution category : Not determined.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Finess Dubbeldek mat (High opacity wall paint)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Contains no REACH Annex XIV substances

VOC content : (cat.A/a): 30 g/l (2010). This product contains max. 5 g/l VOC.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

1.1	Product code	Modified
-----	--------------	----------

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H400	Very toxic to aquatic life
EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request

SDS EU (REACH bijlage II) [NIET VOOR UITGIFTE]

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product