

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : Spraytone Aluzink  
 Product code : 15042090100B  
 Product group : Paint.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
 Main use category : Consumer use, Professional use, Industrial use  
 Use of the substance/mixture : Aerosol.  
 Industrial and decoration painting.

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

International Trading  
 Kobaltweg 3  
 5234 GN 's-Hertogenbosch - Nederland  
 T +31 (0)73 70 70 118

##### Responsible formatting SDS

Mantech Nederland B.V.  
 Kobaltweg 7  
 P.O. Box 39  
 5234 GN 's-Hertogenbosch - Nederland  
 T +31 (0)73 70 70 112 - F +31 (0)73 64 43 861  
[info@mantechbv.nl](mailto:info@mantechbv.nl) - [www.mantechbv.nl](http://www.mantechbv.nl)

#### 1.4. Emergency telephone number

Emergency number : International Trading: +31 (0)73 70 70 118 (08:00 - 17:00)

NL - Nationaal Vergiftigingen Informatie Centrum (NVIC)  
 Emergency telephone (24 hours): +31 30 274 88 88  
 (Only for doctors to inform accidental poisoning)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
 Serious eye damage/eye irritation, Category 2 H319  
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
 Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411  
 Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazardous ingredients : Acetone; Solvent naphtha (petroleum), light arom. (<0.1% benzol CAS nr. 71-43-2)

Hazard statements (CLP) : H222 - Extremely flammable aerosol.  
 H229 - Pressurised container: May burst if heated.  
 H319 - Causes serious eye irritation.  
 H336 - May cause drowsiness or dizziness.

# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Precautionary statements (CLP)	: H411 - Toxic to aquatic life with long lasting effects. P102 - Keep out of reach of children. P260 - Do not breathe spray. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P211 - Do not spray on an open flame or other ignition source. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH210 - Safety data sheet available on request.
Extra phrases	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C Do not pierce or burn, even after use Do not spray on a naked flame or any incandescent material
Security closing plug for children	: Not applicable
Tactile warning	: Not applicable

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8 (REACH-no) 01-2119472128-37	25 - 50	Flam. Gas 1, H220 Press. Gas
Acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	20 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Zinc powder - zinc dust (stabilized)	(CAS-No.) 7440-66-6 (EC-No.) 231-175-3 (EC Index-No.) 030-002-00-7 (REACH-no) 01-2119467174-37	5 - 10	Not classified
Solvent naphta (petroleum), light arom. (<0.1% benzol nr. 71-43-2)	(CAS-No.) 64742-95-6 (EC-No.) 265-199-0 (EC Index-No.) 649-356-00-4 (REACH-no) 01-2119455851-35	5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	2,5 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
aluminium powder (stabilised)	(CAS-No.) 7429-90-5 (EC-No.) 231-072-3;231-072-3b (EC Index-No.) 013-002-00-1 (REACH-no) 01-2119529243-45	2,5 - 5	Flam. Sol. 1, H228
1,2,4-trimethylbenzene	(CAS-No.) 95-63-6 (EC-No.) 202-436-9 (EC Index-No.) 601-043-00-3 (REACH-no) 01-2119472135-42	1 - 2,5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Aquatic Chronic 2, H411
Cumene	(CAS-No.) 98-82-8 (EC-No.) 202-704-5 (EC Index-No.) 601-024-00-X (REACH-no) 01-2119495602-34	0,1 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Propylbenzene	(CAS-No.) 103-65-1 (EC-No.) 203-132-9 (EC Index-No.) 601-024-00-X	0,1 - 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Aquatic Chronic 2, H411
mesitylene, 1,3,5-trimethylbenzene	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5 (REACH-no) 01-2119463878-19	0,1 - 1	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
mesitylene, 1,3,5-trimethylbenzene	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5 (REACH-no) 01-2119463878-19	(C >= 25) STOT SE 3, H335

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice. Symptoms may be delayed. supervision of a doctor is necessary during at least 48h after an accident happenend.
First-aid measures after inhalation	: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.
First-aid measures after skin contact	: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
First-aid measures after eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
First-aid measures after ingestion	: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. Drink plenty of water.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: No information is on file to date regarding acute and/or delayed post-exposure symptoms and effects.
------------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO <sub>2</sub> ), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.
-------------	---

### 5.3. Advice for firefighters

Precautionary measures fire	: Pressurised container: May burst if heated. Cool closed containers exposed to fire with water.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Use personal protective equipment as required.
Emergency procedures	: Do not smoke. Avoid ignition sources. Ventilate area. Do not breathe vapours.

#### 6.1.2. For emergency responders

Protective equipment	: Equip rescue crew with proper protection.
Emergency procedures	: No smoking. Avoid ignition sources. Ventilate area. Do not breathe vapours.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
-------------------------	---

# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Other information : Clean preferably with a detergent - avoid use of solvents.

### 6.4. Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Hygiene measures : Smoking, eating and drinking should be prohibited in application area.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and dry.  
Storage conditions : Observe the label precautions. Store in accordance with local/national regulations.  
Storage temperature : 5 - 30 °C Store in dry, well-ventilated area.  
Heat and ignition sources : Keep away from heat and direct sunlight.  
Information on mixed storage : Not necessary under the recommended storage and handling conditions.  
Storage area : Store in dry, cool, well-ventilated area.

### 7.3. Specific end use(s)

No supplementary information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Acetone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	500 ppm
xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

Zinc powder - zinc dust (stabilized) (7440-66-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	5 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0,83 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,5 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,0206 mg/l
PNEC aqua (marine water)	0,0061 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	117,8 mg/kg dwt
PNEC sediment (marine water)	56,5 mg/kg dwt
PNEC (Soil)	
PNEC soil	35,6 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0,052 mg/l
aluminium powder (stabilised) (7429-90-5)	
DNEL/DMEL (General population)	
Long-term - local effects, inhalation	3,72 mg/m <sup>3</sup> [ REACH Regulations/DNEL, European Chemicals Agency , Regulation (EC) No 1907/2006 ]

# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### Hand protection:

not necessary

#### Eye protection:

Aerosol can. Even though no eye contact is expected under reasonable normal conditions of use, appropriate eye protection should be worn when handling this material.

#### Skin and body protection:

Aerosol can. Protective clothing not absolutely necessary

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Do not breathe gas, fumes, vapour or spray. (Short term exposures: breathing apparatus with filter; long duration exposure: supplied-air respirator)

#### Consumer exposure controls:

Wash hands before break and at end of works. When using do not eat, drink or smoke.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Grey.
Odour	: Characteristic. Propellant spray.
Odour threshold	: No data available
pH	: Not determined.
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: Not applicable, as aerosol.
Flash point	: < 0 °C Not applicable, as aerosol.
Auto-ignition temperature	: The product does not ignites spontaneously.
Decomposition temperature	: When exposed to heat, may decompose liberating hazardous gases
Flammability (solid, gas)	: 240 °C This product is flammable.
Vapour pressure	: 4000 hPa
Relative vapour density at 20 °C	: Not determined.
Relative density	: Not determined.
Density	: ≈ 0,828 g/cm <sup>3</sup> @ 20 °C
Solubility	: Water: Negligible.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: Not determined.
Viscosity, dynamic	: Not determined.
Explosive properties	: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Oxidising properties	: No data available.
Explosive limits	: 2,6 - 26,2 vol %

### 9.2. Other information

VOC content : 669,5 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products. Open flame. Overheating.

### 10.5. Incompatible materials

No supplementary information available.

### 10.6. Hazardous decomposition products

Such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	20000 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	0,039 mg/l/4h

<b>Zinc powder - zinc dust (stabilized) (7440-66-6)</b>	
LD50 oral rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	5,41 mg/l/4h

<b>aluminium powder (stabilised) (7429-90-5)</b>	
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5 mg/l/4h

<b>xylene (1330-20-7)</b>	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	0,0221 mg/l/4h

<b>1,2,4-trimethylbenzene (95-63-6)</b>	
LD50 oral rat	5000 mg/kg

<b>Cumene (98-82-8)</b>	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	12300 mg/kg

<b>Propylbenzene (103-65-1)</b>	
LD50 oral rat	6040 mg/kg

<b>Solvent naphta (petroleum), light arom. (&lt;0.1% benzol CAS nr. 71-43-2) (64742-95-6)</b>	
LD50 oral rat	3592 mg/kg (OECD 401 methode)
LD50 dermal rabbit	> 3160 (OECD 402 methode)
LC50 inhalation rat (Vapours - mg/l/4h)	> 6,193 mg/l/4h

Skin corrosion/irritation : Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin  
pH: Not determined.

Serious eye damage/irritation : The liquid splashed in the eyes may cause irritation and reversible damage.  
pH: Not determined.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Potential adverse human health effects and symptoms : Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The mixture has been assessed following the conventional method of the Regulation (EC) No. 1272/2008 [CLP] and is classified as dangerous for the environment. See Sections 2 and 3 for details.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

<b>dimethyl ether (115-10-6)</b>	
LC50 fish 1	> 4000 mg/l
<b>Acetone (67-64-1)</b>	
LC50 fish 1	5540 mg/l [ 96 h.]
LC50 other aquatic organisms 2	2262 ml/l daphnia
EC50 Daphnia 1	8800 mg/l
<b>Zinc powder - zinc dust (stabilized) (7440-66-6)</b>	
LC50 other aquatic organisms 1	0,57 mg/l [ 96 h., daphnia magna ]
EC50 Daphnia 1	2,8
<b>xylene (1330-20-7)</b>	
LC50 fish 1	13,5 mg/l [ 96 h.]
EC50 Daphnia 1	7,4 mg/l [ 48 h.]
<b>Cumene (98-82-8)</b>	
LC50 fish 1	6,3 - 6,6 mg/l
EC50 Daphnia 1	11,2 - 14,1 mg/l
<b>Solvent naphta (petroleum), light arom. (&lt;0.1% benzol CAS nr. 71-43-2) (64742-95-6)</b>	
LC50 fish 1	3,77 mg/l [96 h.]
EC50 Daphnia 1	150 mg/l [ 24 h.] ( 7,4 mg/l [48 h.] )

#### 12.2. Persistence and degradability

<b>Spraytone Aluzink</b>	
Persistence and degradability	There are no data available on the preparation itself. May cause long-term adverse effects in the aquatic environment.

#### 12.3. Bioaccumulative potential

<b>Spraytone Aluzink</b>	
BCF fish 1	(highly) toxic to fish
Log Pow	No data available
Log Kow	No data available
Bioaccumulative potential	There are no data available on the preparation itself.

#### 12.4. Mobility in soil

<b>Spraytone Aluzink</b>	
Ecology - soil	There are no data available on the preparation itself.

#### 12.5. Results of PBT and vPvB assessment

<b>Spraytone Aluzink</b>	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

#### 12.6. Other adverse effects

Additional information : Product may not flow into sewer or superficial water. May pollute public waters.. Toxic to fish.. (highly) toxic to plankton

# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste)	: Do not allow to enter drains or water courses.
Waste treatment methods	: Recycling is preferred to disposal or incineration.
Product/Packaging disposal recommendations	: Dispose of this material and its container to hazardous or special waste collection point.
Additional information	: Uncleaned packaging: Recommendation: Not completely empty packaging must be treated complying Directive 91/689/EEC.
European List of Waste (LoW) code	: 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 00 00 - WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED 15 01 04 - metallic packaging

### SECTION 14: Transport information

In accordance with ADR

#### ADR

##### 14.1. UN number

1950

##### 14.2. UN proper shipping name

AEROSOLS

##### Transport document description

UN 1950 AEROSOLS (Dangerous for the environment), 2.1, (D), ENVIRONMENTALLY HAZARDOUS

##### 14.3. Transport hazard class(es)

2.1



##### 14.4. Packing group

Not applicable

##### 14.5. Environmental hazards

Dangerous for the environment : Yes

Environmentally hazardous substances: zinc powder - zinc dust (stabilised)

##### 14.6. Special precautions for user

Special transport precautions : Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

##### - Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Transport category (ADR)	: 2
Tunnel restriction code (ADR)	: D

##### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code	: Not usable.
Ship type	: Not determined.
Pollution category	: Not determined.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances



# Spraytone Aluzink

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

VOC content : 669,5 g/l

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
1.1	Product code	Modified	

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*