



Technical datasheet

STAINBLOCKER spray paint 400 ml

Quick drying, white stain blocking primer designed for convenient treatment of small, local areas of the substrate that bleed, such as damp stains, rust patches, soot deposits, adhesive remnants, etc. For interior and exterior use.

Substrate:

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. In the case of exterior applications, remove all moss, mould and algal growth.

Handling:

Carefully cover or mask off the areas that do not require painting. The spray can must be at room temperature (minimum of 15°C). Shake well for at least 3 minutes before use. You should hear the mixing ball rattle loudly. Remove the cap using a screwdriver. Apply in 2 to 3 thin coats at a distance of approx. 30 cm. Start next to the area to be sprayed and move uniformly towards, over and past the relevant area. Turn the spray can upside down after use and spray to expel all remaining paint from the valve. Covers: approx. 1 - 2 m² per 400 ml.

Drying time (at 23°C and relative humidity of 65%): Cured/ready for further coating: after approximately 15 minutes. The drying time depends on the ambient temperature, the relative humidity and the coating thickness.

General:

- It is better to apply several thin layers, instead of one thick layer.
- Work in a well ventilated area. If necessary, use appropriate safety equipment.
- Do not use at temperatures below 10°C., when it is likely to rain, frost is expected, or in direct sunlight.
- Store in a dry, cool and frost-free place.

Technical data

Content	400 ml
Base	Modified Alkyd Resin
Colour	White
Solid components	35 m/m %
General	Do not use at temperatures below 10°C. Do not use outside when it is likely to rain, frost is expected, or in direct sunlight. The spray can must be kept at room temperature (minimum of 15°C). Never place the spray can on a heat source.
Storage	Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.
Surplus product	This paint and the packaging should be disposed of at a collection point for hazardous or special waste.
Hazard classification	See MSDS

The effectiveness of our systems is based on developments in the raw material suppliers' materials and our practical experience. We cannot, however, be held liable without qualification for the work produced based on those systems, as the final result will be determined, in part, by the state of the substrates and other factors that are outside of our control. The current publication makes previously published technical sheets null and void.