

Description: Quick drying, filling acryl primer. For interior use.

Application: For wood, MDF, board, primed metal, plasterwork and rigid plastic.

Properties:

- Quick drying
- Good filler
- Excellent hiding power
- Low in odour and virtually solvent-free
- Easy to sand
- Even coverage
- Insulating

Handling: Stir well before use. Apply 2 reasonably full coats with an acrylic brush/roller or varnish roller. Dilute the first layer on untreated wood with up to 3% of water as required. Apply the second layer undiluted. Lightly sand and remove any dust between the coats. Do not apply to large surfaces simultaneously and always work wet-on-wet due to the quick drying properties of the product.

Covers: Approx. 11-13 m² per litre per coat depending on the object to be painted and the application method.

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 1 hours. Can be painted over after approx. 6 hours, wood types that bleed - after at least 16 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Slightly round off the sharp corners to obtain good edge coverage.

Unpainted wood and MDF: Degrease, sand lightly and remove any dust.

Metal: Degrease, remove all rust and make free of dust. Treat with antirust red oxide primer and, next, apply an intermediate coat of SPS Acrylic Primer.

Rigid plastic: Degrease, remove all dust. Treat with plastic primer and, next, apply an intermediate coat of Finess Acrylic Primer.

Plasterwork: Degrease, sand lightly and remove any dust.

TECHNICAL DATA

Binding agent: Acrylic dispersion

Pigments: Rutile titanium dioxide and mineral extenders

Solvent: Water

Solid components: 53% by weight

SG: Approx. 1.35 g/ml

Viscosity: Krebs Stormer 90 KU @ +20°C

Fineness: 20 microns

Recommended coat thickness: 35 microns dry

Degree of gloss: Matt

Tint: White

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Use water and soap.

Performance: Primer with good filling properties, for interior use. Can even be recoated on the same day.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. After use, close the container correctly and store in an upright position in a frost-free area. Do not close doors and windows until the paint has dried fully (after a minimum of 8 hours).

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.