

Description: White, wear-resistant paint for road markings. Also highly suitable for sealing damp stains, nicotine stains, soot deposits etc. For interior and exterior use.

Use: Intended for use as a coating on concrete and asphalt, and as a sealing agent for damp stains and nicotine stains.

Properties:

- Highly effective sealing
- Quick drying
- Durable
- Good visibility in the dark

Colour: White

Application: Stir well before use. Apply with a flat brush, round brush or airless sprayer.

Covers: Approx. 8m²/litre per coat.

Drying time at 23°C and relative humidity of 65%:

Dust dry after approximately 2 hours.
Can be painted over after approximately 18 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. First, remove all moss and algal growth.

Unprimed stone and asphalt: Degrease, remove all dust.

Used as a sealant: Thoroughly clean substrate with water and a degreaser and allow to dry well. Next, apply 2 coats. Lightly sand and remove any dust between the coats.

TECHNICAL DATA

Binding agent: Modified alkyd resin

Pigments: Titanium dioxide and high-performance fillers

Solvent: White spirit

Solid components: 70% by weight

Sp. Gr.: Approx. 1.3 g/ml

Viscosity: Krebs Stormer 100 KU @ +20°C, thixotropic

Granule size: 6.5 according to Hegman

Degree of gloss: Matt

Tint: White

Dilute with: Paint thinner

Flash point: 22° C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or brush cleaner.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: Should preferably be applied at temperatures between +8°C and +30°C. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.