

Description: Colourless, low-odour, water-based primer for stabilising powdery surfaces. Penetrates deeply into the substrate and enhances adhesion between the top coat and the surface. For interior and exterior use.

Use: Specifically manufactured for lightly powdering or strongly absorbent surfaces. Suitable substrates are: cement and plaster, concrete, brick, etc.

Properties:

- Penetrates easily and deeply into the substrate pores and stabilises the surface.
- Is breathable and quick-drying.
- Improves adhesion to the substrate and the coverage efficiency of the finishing coat

Colour: Colourless

Application: Stir thoroughly prior to use. Apply as an undiluted coat using a brush or a square pasting brush.

Covers: Approx. 6-10 m² /litre, strongly dependent on substrate porosity.

Drying time at 23°C and relative humidity of 65%:

Dust-free: After approximately 1 hours.
Can be painted over: After approximately 4 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be smooth, clean, dry and free from dust or grease. Repair cracks and fissures. Remove and repair all loose and unstable layers. First, remove all moss, mould and algal growth when using outdoors.

Powdering, porous and absorbent substrates: Clean thoroughly with water and degreasing agent, let the surface dry. Next, apply a coat of Finess Fixator. If a decorative plaster finish is to be used, paint with a further coat of Finess Decorative Plaster Primer. For optimum adhesion on wall paint, apply a coat of Finess Wall Paint Primer.

Non water-resistant (rub-resistant) layers: Clean thoroughly with water until the surface does not flake or dust any more. Next, apply Finess Fixator after allowing the surface to dry. If a decorative plaster finish is to be used, paint with a further coat of Finess Decorative Plaster Primer. For optimum adhesion on wall paint, apply a coat of Finess Wall Paint Primer.

TECHNICAL DATA

Binding agent: Acrylic dispersion

Solvent: Water

Solid components: 12% by weight

Sp. Gr.: Approx. 1 g/ml

Viscosity: 20 sec Din cup 4 @ +20°C

Tint: Colourless

Dilute with: Do not dilute!

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Water and soap

Performance: Completely stabilises the substrate to ensure it can be coated without problems. Increases the efficiency of subsequent coats.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: Stabilising primer is not a sealing primer. Do not apply multiple layers as the substrate becomes excessively glossy, leading to reduced adhesion. Do not apply outdoors when it is likely to rain or when frost is expected. Do not apply outdoors in direct sunlight. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.