

Description: Satin gloss, opaque, decorative stain. Moisture-regulating and water-repellent. Penetrates well into the wood, has excellent adhesion properties and is resistant to all weather conditions. Does not flake and fade.

Use: Suitable for external use such as wooden wall cladding, fascias, doors, window frames etc.

Properties:

- Water-based
- Moisture-regulating
- Weather-resistant.
- Economical to apply
- Very easy to apply
- Satin gloss

Covers: Approx. 12 m²/litre per coat depending on the object to be painted and the application method.

Directions for use

Stir thoroughly prior to use. Only dilute with 5 - 10% water if applying with a spray gun. Apply in 2 or 3 coats in the direction of the grain using a suitable flat/round brush. Lightly sand in the direction of the grain between coats and wipe off any dust residue before applying the next coat.

Preparation

The surface must be clean and free of dust and grease. Carefully remove green algae and moss.

Unprimed wood:

Degrease using water and ammonia (use thinner for merbau and meranti), slightly break sharp edges, sand lightly in the direction of the grain and remove any dust residue.

Treated wood in good condition: Degrease, sand lightly in the direction of the grain and wipe off any dust residue.

Treated wood in poor condition: Remove old coats using paint stripper, by scraping or sanding and prepare in the same way as unprimed wood.

TECHNICAL DATA

Binding agent: Acrylic dispersion and PU-modified alkyd emulsion

Pigments: Rutile titanium dioxide and colour pigments

Solvent: Water

Solid components: 40% volume

Sp. Gr.: Approx. 1.25 g/ml

Granule size: 15 microns

Recommended layer thickness: 35 microns (dry)

Degree of gloss: Satin gloss

Tint: White and various colours

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Use water and soap.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: We recommend applying at temperatures between +8°C and +30°C. Do not apply in direct sunlight or when it is likely to rain. After use, close the container correctly and store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.