

Description: Acrylic-based wall varnish with glitter gloss. For a sparkling finish of painted walls and wood. Also protects walls painted in a dark colour, against white striping and pollution. For interior use.

Application: Can be applied to painted walls and wood.

Properties:

- Water bourne
- Quick drying
- Decorative
- Non yellowing
- Perfect flow-out upon application
- Gloss

Effect colour: Available in Gold and Mixed colors

Handling: Stir thoroughly prior to use. Apply 1 or 2 coats using an acrylic paint brush, acrylic paint roller or paint sprayer. Do not dilute. Always apply wet-in-wet to avoid visible strokes.

Covers: Approx. 18 m²/litre per coat depending on the object to be painted and the application method.

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 1 hour.
Second layer after approx. 4 hours.

SYSTEM CONSTRUCTION

Substrate: Surfaces must be clean, dry and free from dust or grease.

Untreated wood: Degrease, sand lightly and remove any dust. Round off sharp edges to maximize adhesion. Next apply 2 or 3 coats wall varnish.

Painted walls: Carefully degrease with a degreasing agent and water.

TECHNICAL DETAILS (Gold and Mix Effect)

Binding agent: alkyd emulsion

Pigments: none

Solvent: Water

Solid components: Approx. 26% by volume

SG: Approx. 1 g/ml

Viscosity: Krebs Stormer 85-90 KU @ +20°C

Recommended coat thickness: 35 microns per coat (dry)

Degree of gloss: 60% with Gardner 60° gloss meter

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Use water and soap.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. After use, close the container correctly and store in an upright position in a frost-free area.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.