

Description: Durable, moisture-controlling, good covering gloss wood stain based on alkyd resin. Offers 4 years of protection to all sorts of wood.

Application: For windows, doors, wooden wall claddings etc.

Properties:

- Moisture-controlling
- Weather-resistant.
- Water repellent
- 4-year durability

Colours: White and various colours.

Handling: Stir thoroughly prior to use. Apply with a brush. Retouch large surfaces with a roller. Apply 3 coats on unprimed wood and 1 or 2 coats when carrying out maintenance. Dilute the first coat on unprimed wood with 5% white spirit. Do not dilute the following coats. Sand lightly between coats and remove any dust.

Covers: Approx. 15 m²/litre per coat, depending on the surface.

Drying time at 23°C and relative humidity of 65%:
Dust-dry after approx. 4 hours.
Can be painted over after approx. 18 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be firm, clean, dry and free from dust or grease

Unprimed wood: Degrease, lightly sand down, round of any sharp edges and repair open wood joints, sealed joints and such with a suitable product. After hardening, sand it all down and make it free from dust.

Treated wood in poor condition: Remove all poorly adhering paint using paint stripper or a blowtorch/hot air paint removal gun. Then treat as "Unprimed wood".

Treated wood in good condition: Degrease with a degreasant and allow to dry. Then lightly sand down and retouch where required.

Old acrylic paint or acrylic non-transparent stain coats (water-soluble): Remove completely.

TECHNICAL DETAILS (colour white)

Binding agent: Glycerophthalic resins

Pigments: Rutile titanium dioxide and colour pigments

Solvent: White spirit

Solid components: 64% by volume

SG: Approx. 1 – 1.22 g/ml

Viscosity: ICI Rot thinner 8 Poise @ +20°C

Fineness: 15 microns

Recommended coat thickness: 3 x 35 microns (dry)

Degree of gloss: Gloss. 70-85% with Gardner 60° gloss meter

Tint: White and various colours

Dilute with: White spirit

Flash point: 39°C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or brush cleaner

Features: Microporous: moisture-permeable, allows the wood to breathe.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. Do not apply in direct sunlight or when it is likely to rain. After use, close the container correctly, turn it around for a few seconds to ensure that skin formation cannot occur and store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.