

Description: Matt, solvent-free wall paint based on a synthetic resin dispersion, specifically designed for painting walls and ceilings in large-scale new construction and renovation projects. Can be applied universally in dry areas. For interior use.

Use: As a wall paint on mineral substrates for renovation and new-construction projects. Suitable surfaces include: existing coats of wall paint, cement and plasterwork, concrete, brick, gypsum panelling, board etc. Also suitable for painting glass fibre fabric.

Properties:

- Real-estate project quality
- Easy to apply.
- High financial return
- Good hiding capacity
- Easy to wash
- Matt

Colour: White and can be tinted using universal colour pastes.

Application: Stir thoroughly prior to use. The first coat can be diluted with a maximum of 10% water. Apply in 1 or 2 coats using a suitable brush, paint roller or paint sprayer. Always work wet-on-wet to prevent visible marks in the paint. Back-roll all overlaps in the same direction. Do not touch up when drying.

| | | |
|----------------|-------------------------|----------------------|
| Spraying: | airless | airmix |
| Nozzle opening | 0.017-0.019" | 0.017-0.019" |
| Pressure | approx. 220 - 250 bars. | approx. 150-180 bars |
| Air pressure | - | approx. 2 bars. |

The stated settings for spraying this product should be taken as your starting point. Depending on the on-site conditions, the settings will have to be determined by the person applying the paint.

Covers: approx. 7 m² /litre per coat. The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

Drying time at 23°C and relative humidity of 65%:

Dry: after approx. 2 hours.

Can be painted over after approximately 4 to 6 hours.

Variations in coating thickness, temperature, humidity etc. affect the drying time.

SYSTEM CONSTRUCTION

General:

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

New, untreated substrates

- Prime (highly) absorbent surfaces in their entirety using SPS Fixator.
- Thoroughly clean powdery surfaces. Prime using Fixator after allowing to dry.
- Apply the top coat after allowing to dry.

Existing intact coats of wall paint

- Clean.
- Apply an intermediate coat of SPS Projecttex 1010 if necessary.
- Apply the top coat after allowing to dry.

Existing, flaking coats of wall paint

- Remove loose parts.
- Thoroughly wash powdery coats and allow them to dry.
- Carry out any repairs.
- Prime with SPS Fixator.
- Apply the top coat after allowing to dry.

Stains caused by nicotine, damp, rust or soot

- Clean thoroughly.
- Treat surface/stain with SPS Insulator.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA (apply to the colour white)

| | |
|------------------------------------|---|
| Binding agent: | Solvent-free synthetic resin dispersion |
| Pigments: | Rutile titanium dioxide and mineral fillers |
| Solvent: | Water |
| Solid components: | 40 % v/v |
| Equivalent weight: | Approximately 1.55 g/ml |
| Recommended coat thickness: | Dry coating thickness/coat: 60 micrometres Wet coating thickness/coat: 150 micrometres |
| Degree of gloss: | Matt: 9% @ 85° |
| Dilute with: | Water |
| Hazard classification: | See MSDS |
| Tool cleaning instructions: | Use water and soap. |

Shelf life: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General:

The values stated in this technical data sheet have been determined based on DIN EN 13300. Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Always use the required personal protective equipment when applying this product. Do not inhale spray mist/fumes given off by products. Always ventilate appropriately when applying.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.