

**Description:** Matt wall paint with excellent hiding power and a very long open time, based on a synthetic resin dispersion. Prevents colour variations between strokes, good flow. Solvent-free and preserves the texture of the substrate. Designed specifically to provide a smooth finish on highly absorbent surfaces such as plasterwork and spray plaster (spackling). For interior use.

**Use:** Meant, in particular, for surfaces that have very strong suction properties such as spray plaster (spackling) and gypsum plaster. Suitable substrates are untreated absorbent cement plaster and gypsum plaster, brickwork.

**Properties:**

- Long open time
- Avoids significant colour differences between strokes
- Extra matt
- Excellent hiding capacity
- Hides small irregularities in the substrate
- Solvent-free

**Colour:** White and in light colours in the SPC Color Service colour mixing system.

**Application:**

Stir thoroughly prior to use. The first coat can be diluted with a maximum of 10% water. Apply in 1 or 2 coats using a suitable brush or paint roller. Always work wet-on-wet to prevent marks in the paint. Back-roll all overlaps in the same direction. Do not touch up when drying.

**Covers:** approx. 7 m<sup>2</sup>/litre per coat. The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

**Drying time at 23°C and relative humidity of 65%:**

Dry after approximately 2 hours.

Can be painted over after approximately 6 hours.

Variations in coating thickness, temperature, humidity, etc. affect the drying time.

### SYSTEM CONSTRUCTION

**General:**

The surface must be capable of supporting the paint, completely set, clean, dry, and free of dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

**New, untreated substrates**

- Paint absorbent substrates in their entirety with SPS Spacktex 3535.
- Thoroughly clean powdery surfaces. Prime using Fixator after allowing to dry.
- Apply the top coat after allowing to dry.

**Contamination caused by nicotine, damp, rust or soot**

- Clean thoroughly.
- Treat surface/stain with SPS Insulator.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA (apply to the colour white)

<b>Binding agent:</b>	Synthetic resin dispersion
<b>Pigments:</b>	Rutile titanium dioxide and fine fillers
<b>Solvent:</b>	Water
<b>Solid components:</b>	40 % v/v
<b>Specific mass:</b>	approx. 1.43 g/ml
<b>Recommended coat thickness:</b>	Dry coating thickness/coat: approx. 55 micrometres Dry coating thickness/coat: approx. 140 micrometres
<b>Degree of gloss:</b>	Extra matt: 1% @ 85°
<b>Dilute with:</b>	Water
<b>Hazard classification:</b>	See MSDS
<b>Tool cleaning instructions:</b>	Use water and soap.

**Shelf life:** Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

**General:**

The values stated in this technical data sheet have been determined based on DIN EN 13300. Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

**Surplus product:** This product and the packaging should be disposed of at a collection point for hazardous or special waste.