

Description: Matt wall paint with excellent hiding power, easily cleanable, based on synthetic resin dispersion. For interior use.

Application: For interior walls and ceilings. Less suitable for rooms that become damp and moist such as kitchens and bathrooms. Suitable substrates are: Cement and plasterwork, concrete, brick, plasterboard, board, wallpaper etc.

Properties:

- Excellent hiding capacity
- Easy to wash
- Easy to apply

Colours: White. Can be tinted by using universal tinting bases.

Handling: Stir thoroughly prior to use. Dilute the first coat with no more than 10% of water if required. Apply the second layer undiluted. Apply 1 or 2 coats using a woolly roller, particularly if applying on rough surfaces. Use a brush for corners etc.

Covers: According to ISO-6504-3 and DIN EN13300 approx. 8m²/litre per coat, depending on the surface. Deposition efficiency: class 2

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 2 hours.
Can be painted over after approx. 5 hours.

SYSTEM CONSTRUCTION

New plasterwork: Prime with Finess Wall Paint Primer or Finess Transparent .

Existing plasterwork: Clean using water and a degreasing agent. Allow to dry. Prime with Finess Wall paint Primer.

Powdery substrates: Clean thoroughly with clean water and allow to dry. Prime with Finess Stabilising Primer.

Non water-resistant (rub-resistant) coats of paint:

Wash thoroughly until the surface does not flake or dust anymore. Next, prime with Finess Stabilising Primer.

Concrete: Remove any 'cement skin' and dust thoroughly using a brush. Next prime the surface with Finess Wall Paint Primer.

Aerated (cellular) concrete blocks: Prime using a special priming agent. Next, apply a coat of plaster. After drying, prime the surface with Finess Wall Paint Primer.

Plasterboard: Bridge the joints with plaster mesh tape and fill with a suitable filler. After allowing to dry: Next prime the surface with Finess Wall Paint Primer..

MDF, chipboard and fibreboard: Sand smooth boards, remove any dust and seal the surface using Finess Sealing Primer.

Load-bearing coats of paint: Clean using water and a degreasing agent. First, sand down glossy coats of paint until matt and carefully ensure the substrate is free of dust.

Substrates stained by nicotine, damp, rust or soot:

Wash with water and a degreasing agent and allow to dry well. Next, seal the surface of the substrate with Finess Sealing Primer.

TECHNICAL DATA

Binding agent: Vinyl copolymer dispersion

Pigments: Rutile titanium dioxide, fine extenders and pigments

Solvent: Water

Solid components: 63% by weight

SG: Approx. 1.55 g/ml

Viscosity: Viscolab LC 3: 5 PaS @ 20°C

Fineness: 50 microns

Degree of gloss: Matt ISO-2813 and DIN EN 13300: 60°/2,5% 85°/9%

Tint: White

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Water

Features: Washability according to DIN 53778: 4000 cycles. 5000 cycles class W abrasion resistance to ISO-11998 and DIN EN 13300: class 3

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Do not use at temperatures below +8°C. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.