

Description: Non-yellowing, quick drying, high gloss top coat enamel based on a synthetic resin dispersion, for radiators and heating pipes. For interior use.

Application: Specifically intended for a decorative finish on radiators and hot water pipes.

Properties:

- Odourless and solvent-free
- Water-soluble
- Quick drying
- Does not yellow
- Environmentally friendly

Colours: White and various colours.

Handling: Stir thoroughly prior to use. Apply a relatively generous coat with a flat or round acrylic paint brush, paint roller or paint sprayer. Dilute the first layer with 5% of water as required. Apply the second layer undiluted. Sand lightly between coats and remove any dust. Do not apply to large surfaces simultaneously and always work wet-on-wet due to the quick drying properties of the product.

Covers: Approx. 16 m²/litre per coat.

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 1 hours.
Can be painted over after approx. 6 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease.

Untreated radiators: Degrease, lightly sand and remove any dust. Prime first with Finess Anti corrosive primer.

Paint surfaces in good condition: Degrease, lightly sand and remove any dust.

Surface in poor condition: Remove old coats and treat as "Untreated radiators".

TECHNICAL DATA

Binding agent: Acrylic dispersion

Pigments: Titanium dioxide

Solvent: Water

Solid components: 35% by volume

SG: Approx. 1.3 g/ml

Viscosity: Krebs Stormer 70 KU @ +20°C

Fineness: 6 using Hegman gauge

Recommended coat thickness: 35 microns (dry)

Degree of gloss: Gloss, 85% with Gardner 60° gloss meter

Tint: Various colours

Dilute with: Water

Features: Non-yellowing, excellent adhesion.

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Use water and soap.

Features: Non-yellowing, excellent adhesion.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Should preferably be applied at temperatures between 8°C and + 30°C. Shut off radiators before painting and wait for approximately 72 hours before using them again. Do not pour dirty washing water into drains; treat as chemical waste.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.