

Description: Weather-resistant latex paint with good covering power, based on synthetic resin dispersion. For interior and exterior use.

Use: Exterior: for a durable finish on façades. Interior: for painting walls and ceilings in wet rooms. Suitable substrates are: cement and plasterwork, concrete, brickwork, plasterboard, board, wallpaper, etc.

Properties:

- Scrub-resistant
- Matt
- Durable
- Easy to apply

Colour: White, can be tinted by using universal tinting pastes if required.

Application: Stir thoroughly prior to use. Dilute the first coat with no more than 10% of water as required. Apply the second coat undiluted. Apply with a brush, woolly roller or airless spray.

Covers: According to ISO-6504-3 and DIN EN 13300 approx. 8 m²/l, depending on the substrate. Effective coverage: class 3

Drying time at 23°C and relative humidity of 65%:
Dry after approximately 2 hours.
Can be painted over after approximately 4 to 6 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Repair cracks and fissures. Remove and/or repair all loose and unstable coats. First, remove all moss, mould and algal growth when using outdoors.

New plasterwork: Interior: prime with Finess Wall Paint Primer or Finess Transparent Primer. Exterior: prime with Finess Fixator.

Existing plasterwork: Clean using water and a degreasing agent. Allow to dry. Interior: prime with Finess Wall Paint Primer or Finess Transparent Primer. Exterior: prime with Finess Fixator.

Powdery substrates: Clean thoroughly with clean water and allow to dry. Prime with Finess Fixator.

Non water-resistant (rub-resistant) coats of paint:
Wash thoroughly until the surface does not flake or powder any more. Next, prime with Finess Fixator.

Concrete: Remove any 'cement skin' and dust thoroughly using a coarse brush. Next prime the surface with Finess Wall Paint Primer or with an initial coat of diluted Finess Wall Paint Façade Acrylic.

Plasterboard: Bridge the joints with plaster mesh tape and fill with a suitable filler. After drying, prime the surface with Finess Wall Paint Primer or with an initial coat of diluted Finess Wall Paint Façade Acrylic.

MDF, chipboard and fibreboard: Sand the boards smooth, remove any dust and seal the surface using Finess Isolator.

Intact coats of paint in good condition: Clean using water and a degreasing agent. First, sand glossy coats of paint until matt and carefully remove any dust.

Substrates stained by nicotine, damp, rust or soot:
Wash with water and a degreasing agent and allow to dry well. Next, seal the surface of the substrate with Finess Isolator.

TECHNICAL DATA

Binding agent: Styrene acrylate dispersion

Pigments: Rutile titanium dioxide and mineral fillers

Solvent: Water

Solid components: 40% in volume

Sp. Gr.: Approx. 1.45 g/ml

Viscosity: Viscolab LC 3: 5.5 PaS @ 20°C

Granule size: 50 microns

Degree of gloss: Matt ISO-2813 and DIN EN 13300: 60°/ 2° 85°/ 6%

Tint: White

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Water and soap

Performance: Washability according to DIN 53778: minimum of 5000 cycles, class S. Scrub resistance to ISO-11998 and DIN EN 13300, class 2.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: Stir thoroughly prior to use. Do not apply at temperatures below +8°C, in direct sunlight or when rain is expected. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.