

Description: High quality, satin gloss 100% acrylic wall paint, especially designed for walls and ceilings in kitchens and bathrooms. Virtually odour-free and easy to wash down whenever required. For interior use.

Application: For interior walls and ceilings when a colour finish is required. Suitable substrates are: Cement and plasterwork, concrete, brick, plasterboard, board, wallpaper etc.

Properties:

- Good hiding capacity
- For damp areas
- Very easy to wash down
- Easy to apply

Colours: Various colours

Handling: Stir thoroughly prior to use. Dilute the first coat with no more than 10% of water if required. Apply the second layer undiluted. Apply 1 or 2 coats using a woolly roller, particularly if applying on rough surfaces. Use a brush for corners etc.

Covers: According to ISO-6504-3 and DIN EN13300 approx. 8m²/litre per coat, depending on the surface. Deposition efficiency: Class 3

Drying time at 23°C and relative humidity of 65%:
Dust-dry after approx. 2 hours.
Can be painted over after approx. 6 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

New plasterwork: Prime with Finess Wall Paint Primer or Finess Transparent .

Existing plasterwork: Clean using water and a degreasing agent. Allow to dry. Prime with Finess Wall paint Primer.

Powdery substrates: Clean thoroughly with clean water and allow to dry. Prime with Finess Stabilising Primer.

Non water-resistant (rub-resistant) coats of paint: Wash thoroughly until the surface does not flake or dust anymore. Next, prime with Finess Stabilising Primer.

Concrete: Remove any 'cement skin' and dust thoroughly using a brush. Next prime the surface with Finess Wall Paint Primer.

Aerated (cellular) concrete blocks: Prime using a special priming agent. Next, apply a coat of plaster. After drying, prime the surface with Finess Wall Paint Primer.

Plasterboard: Bridge the joints with plaster mesh tape and fill with a suitable filler. After allowing to dry: Next prime the surface with Finess Wall Paint Primer..

MDF, chipboard and fibreboard: Sand smooth boards, remove any dust and seal the surface using Finess Sealing Primer.

Load-bearing coats of paint: Clean using water and a degreasing agent. First, sand down glossy coats of paint until matt and carefully ensure the substrate is free of dust.

Substrates stained by nicotine, damp, rust or soot: Wash with water and a degreasing agent and allow to dry well. Next, seal the surface of the substrate with Finess Sealing Primer.

TECHNICAL DATA

Binding agent: Acrylic dispersion

Pigments: Rutile titanium dioxide, fine extenders and pigments

Solvent: Water

Solid components: 45% by volume

SG: Approx. 1.3 g/ml

Viscosity: Viscolab LC 3: 6 PaS @ 20°C

Fineness: 50 microns

Degree of gloss: Mid-gloss ISO-2813 and DIN EN 13300: 60°/26% 85°/60%

Tint: Various colours

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Use water and soap.

Features: Washability according to DIN 53778: >5000 cycles: Class S Scrub-resistance to ISO-11998 and DIN EN 13300: class 2

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Do not use at temperatures below +8°C. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.