

Description: Water-based sealing primer based on acrylic resin. For interior and exterior use.

Use: Specially manufactured for treating difficult-to-remove contamination and stains on the substrate such as damp stains, nicotine and soot deposits and glue residues which may "bleed" through the finishing coat.

Properties:

- Perfect sealing properties
- Water-based
- Virtually odourless
- Easy to apply.

Colour: White

Application: Stir well before use and do not dilute! Apply in at least 2 coats using a brush or square whitewash brush. Wait for at least 24 hours between coats.

Covers: Approx. 6-10 m²/litre per coat, depending on the surface.

Drying time at 23°C and relative humidity of 65%:

Dry after approximately 3 hours.
Can be painted over after complete curing (approx. 24 hours).

SYSTEM CONSTRUCTION

Substrate: The surface must be smooth, clean, dry and free from dust or grease. Repair cracks and fissures. Remove and repair any loose and unstable coats. When using outdoors, remove all moss, mould and algal growth first.

Substrates contaminated by nicotine, damp, rust or soot, etc.: Wash with water and a degreasant and allow to dry well. Next, seal the stain area with Finess Isolator. If a decorative plaster finish is to be used, paint with a further coat of Finess Decorative Plaster Primer and for optimum adhesion on wall paint, apply a coat of Finess Wall Paint Primer.

MDF, chipboard, etc.: Lightly sand the area, remove any dust residue and seal using Finess Isolator. If a decorative plaster finish is to be used, paint with a further coat of Finess Decorative Plaster Primer and for optimum adhesion on wall paint, apply a coat of Finess Wall Paint Primer.

TECHNICAL DATA

Binding agent: Acrylic dispersion

Pigments: Rutile titanium dioxide and special lamellar platelet fillers

Solvent: Water

Solid components: 52% by weight

Sp. Gr.: Approx. 1.3 g/ml

Viscosity: 50 - 60 Poise Brookfield Sp6/50rpm

Degree of gloss: Matt

Tint: White

Dilute with: Do not dilute.

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Water and soap

Performance: Seals damp stains, soot and nicotine deposits, glue residues, etc. Can be painted over with latex paint etc.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: Stir thoroughly prior to use. Do not apply at temperatures below +8°C, in direct sunlight or when rain is expected. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.