

Description: Satin gloss, colourless stair lacquer based on synthetic resin dispersion. In gel form to keep dripping and sagging to a minimum. For interior use.

Use: For the long-lasting protection of stairs but also for other wood such as skirting boards, doors, furniture, etc.

Properties:

- In gel form
- Hard-wearing and durable
- Satin gloss
- Virtually odourless
- Reinforced with polyurethane

Colour: Colourless

Application: Stir gently before use. Do not dilute. Apply in the direction of the grain using a broad acrylic brush or acrylic roller. After each coat, sand lightly in the direction of the grain and carefully remove any dust. Never touch up lacquer that is already drying. Because it is quick-drying, do not paint excessively large areas in one go and always use the wet-on-wet method.

Covers: Approximately 11m²/litre per coat.

Drying time at 23°C and relative humidity of 65%:

Dust dry after approximately 1 hour.
Can be painted over after approximately 4 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Completely remove poorly adhering coats of varnish.

Untreated stairs: Clean with water and a degreasing agent, sand lightly and remove any dust. Repair any holes using wood filler putty. Finish with 3 coats of Finess Stairway Varnish.

Untreated furniture, doors and skirting boards: Clean with water and a degreasing agent, sand lightly and remove any dust. Repair any holes using wood filler putty. Finish with 2 coats of Finess Stairway Varnish.

Treated wood in good condition: Carefully remove any grease using a degreasing agent. Remove any layers of wax using paraffin. Sand lightly and remove any dust. Finish with 1 or 2 coats of Finess Stairway Varnish.

Old coats of varnish in poor condition: Completely remove coats of varnish by sanding right down and/or scraping off. Then treat as "Untreated wood".

TECHNICAL DATA

Binding agent: Acrylic urethane dispersion

Solvent: Water

Solid components: 32% by volume

Sp. Gr.: Approximately 1.05 g/ml

Viscosity: 40 Poise Brookfield Sp6/50rpm

Degree of gloss: Satin gloss, 35-50% with Gardner 60°C gloss meter

Tint: Colourless

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Water and soap

Performance: Gel-type lacquer, scratch-resistant and highly resistant to chemicals.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: It is preferable to use the product in temperatures between + 8°C and + 30°C. Seal the packaging firmly after use and store in a frost-free place in an upright position.

Surplus product: This product and the packaging should be disposed of at a collection point for hazardous or special waste.