TECHNICAL DATA SHEET



Wall varnish Extra Matt/Gloss

Description: Water-based, non-yellowing, colourless wall varnish. Quick-drying and solvent-free. Makes painted walls easier to clean and darkly painted walls more resistant to white marks. Darker colours appear more intensive in colour. For interior use.

Application: painted walls and wood.

Properties:

- Transparent
- Water-based
- Quick drying
- Does not yellow
- Low in odour and virtually solvent-free
- Even coverage
- Extra matt and gloss
- For internal use

Colours: Colourless.

Handling: Stir well before use. Apply 1 or 2 coats using an acrylic brush or roller. Do not dilute.

Always work "wet-on-wet" to ensure sticking does not occur. Painted walls do not need to be sanded. Lightly sand wooden surfaces between coats and remove any dust.

Covers: Approx. 16-20 m²/litre per coat, depending on the surface and the application method.

Drying time at 23°C and rel. humidity 65%:

Dust-dry after approx. 1 hours. Recoatable after approx. 4 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must have a bearing capacity, be clean, dry, and be free from dust or grease. Sand and repair surface irregularities.

Remove and restore any loose and unstable coats.

Unpainted wood: Degrease, sand lightly and remove any dust. Slightly round off the sharp corners to obtain good edge coverage. Then apply 2-3 layers.

Painted (latex) walls: No specific pre-treatment.

TECHNICAL DATA

Binding agent: Styrene-acrylate

Pigments: Transparent

Solvent: Water

Solid

components: Extra Matt: 28 v/v %

Gloss: 26 v/v%

S.M.: approx. 1 g/ml

Viscosity: Krebs Stormer 85-90 KU @ +20°C

Recommended

coat thickness: 35 microns (dry)

Gloss degree: Extra matt 5% (Gardner 85°)

Gloss 60% (Gardner 60°)

Tint: Colourless

Dilution: Do not dilute.

Hazard

classification: See MSDS

Cleaning

instructions: Use water and soap.

Storage: Minimum 12 months in tightly closed original packing in a dry, cool and frost-free place.

General: Do not apply in temperatures below +8°C, in direct sun or when rain is possible. Keep out of reach of children.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.