

QUICK-DRYING SEALING PRIMER

Description: Fast-drying insulator specially designed for convenient treatment of small, local areas of the substrate that bleed, such as damp stains, rust patches, soot deposits, adhesive remnants, etc. For interior and exterior use.

Use: As a pretreatment on a sufficiently thick coating of (wall) paint and mineral substrates that are contaminated by water stains, nicotine, grease and soot deposits, traces of adhesive, etc. In the case of old layers of wallpaper, make sure that the wallpaper adheres adequately to the substrate. Old layers of vinyl wallpaper may contain plasticisers which slow paint drying.

Properties:

- Effective sealing
- Wear-resistant
- Non-saponifiable
- Low surface tension and virtually odourless
- Water-resistant
- Perfectly washable

Colour: White.

Application: Carefully cover or mask off the areas that do not require painting. The spray can must be at room temperature (minimum of 15°C). Shake well for at least 3 minutes before use. You should hear the mixing ball rattle loudly. Remove the cap using a screwdriver. Apply in 2 to 3 thin coats at a distance of approx. 30 cm. Start next to the area to be sprayed and move uniformly towards, over and past the relevant area. Turn the spray can upside down after use and spray to expel all remaining paint from the valve.

Covers: 1 - 2 m² per coat. The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

Drying time at 23°C and relative humidity of 65%:

Dry and ready to be painted after approx. 15 minutes.

Variations in coating thickness, temperature, humidity, etc. affect the drying time.

SYSTEM CONSTRUCTION

General:

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. In the case of exterior applications, remove all moss, mould and algal growth.

Stains caused by nicotine, damp, rust or soot

- Clean thoroughly using SPS Paint cleaner.
- Treat surface/stain with SPS Fast-drying sealing primer.

The system described above applies for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

QUICK-DRYING SEALING PRIMER

TECHNICAL DATA (apply to the colour white)

Binding agent:	Modified alkyd resin
Pigments:	Titanium combined with sealing fillers
Solvent:	Acetone/white spirit
Solid components:	35 m/m %
Specific mass:	Approximately 1.1 g/ml
Hazard classification:	See MSDS

Shelf life: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain, when frost is expected or in direct sunlight. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.
The spray can must be kept at room temperature (minimum of 15°C). Never place the spray can on a heat source and never spray in the direction of a naked flame or red hot objects.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.