



SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Reference number: SDST8b
Issue date: 16/07/2013 Revision date: 25/07/2022 Supersedes version of: 04/10/2021 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : SPS Isomat plus
Product code : 2500053190101
Product group : Wallpaint.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use, Industrial use
Use of the substance/mixture : Industrial and decoration painting.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

SPS BV (SPS)
Zilverenberg, 16
P.O. Box 39 5201 AA 's-Hertogenbosch
NL- 5234 GM 's-Hertogenbosch
Nederland
T +31 (0)73 642 27 10 - F +31 (0)73 642 60 95
info@spsbv.com - www.spsbv.com

Responsible formatting SDS

rmeurohas@rustoleum.eu

1.4. Emergency telephone number

Emergency number : SPS BV.: +31 (0)73 642 27 10 [7:30 - 16:30]

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May EEUH208
produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do EEUH211
not breathe spray or mist.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : Not applicable
Hazard statements (CLP) : Not applicable.
Precautionary statements (CLP) : P102 - Keep out of reach of children.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, eye protection.
P501 - Dispose of contents/container to hazardous or special waste collection point, in
accordance with local, regional, national and/or international regulation.
[Spray application; P261 - Avoid breathing spray.].
EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce
an allergic reaction.

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

EUH210 - Safety data sheet available on request.

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Child-resistant fastening : Not applicable

Tactile warning : Not applicable

2.3. Other hazards

Other hazards which do not result in classification : None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc substance with national workplace exposure limit(s) (NL)	CAS-No.: 14807-96-6	2.5 – 10	Not classified
Kaolin, calcined substance with national workplace exposure limit(s) (NL)	CAS-No.: 92704-41-1	2.5 – 10	Not classified
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	$0,005 \leq C < 0,05$	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400

Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	($0.05 \leq C < 100$) Skin Sens. 1, H317

Comments : This mixture contains $\geq 1\%$ titanium dioxide (CAS 13463-67-7). The Annex VI classification of Titanium dioxide does not apply to this mixture according to its Note 10
There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Full text of H- and EUH-statements: see section 16

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
First-aid measures after skin contact	: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. If skin irritation or rash occurs: Get medical advice/attention. Thoroughly clean shoes before re-using.
First-aid measures after eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
First-aid measures after ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: No information is on file to date regarding acute and/or delayed post-exposure symptoms and effects.
Symptoms/effects after inhalation	: Unwanted symptoms may include the following: irritation of the respiratory tract coughing nausea or vomiting headache drowsiness/fatigue dizziness/twistiness unconsciousness.
Symptoms/effects after skin contact	: Effects of skin contact may include : redness. Irritation. Cracking of the skin. Dry skin.
Symptoms/effects after eye contact	: No specific data.
Symptoms/effects after ingestion	: No specific data.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Immediate specific treatment is necessary in case of poisoning.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: An impenetrable black smoke is produced in the event of a fire. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.
-------------	--

5.3. Advice for firefighters

Precautionary measures fire	: Cool closed containers exposed to fire with water.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses.

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk on the spilled product. Wear suitable protective clothing, gloves and eye/face protection.
- Emergency procedures : Do not smoke. Ventilate area. Do not breathe vapours.

6.1.2. For emergency responders

- Protective equipment : Equip rescue crew with proper protection.
- Emergency procedures : No smoking. Ventilate area. Do not breathe vapours.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Collect spillage.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak without risks if possible.
- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
- Other information : Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep container tightly closed. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. For personal protection see Section 8. Comply with the health and safety at work laws.
- Hygiene measures : Smoking, eating and drinking should be prohibited in application area. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed and dry. Use appropriate container to avoid environmental contamination.
- Storage conditions : Store in accordance with local/national regulations.
- Storage temperature : 5 - 30 °C Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight
- Information on mixed storage : Store separately from oxidising agents and strongly alkaline and strongly acidic materials.
- Storage area : Prevent unauthorised access.
- Special rules on packaging : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store in open, inadequate, mislabeled packaging.

7.3. Specific end use(s)

No additional information available

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. In case of splash hazard: safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Use safety eyewear designed to protect against splash of liquids. Protective goggles (EN 166)

8.2.2.2. Skin protection

Skin and body protection:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Every part of the skin which had contact with the product should have been washed thoroughly. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Wear overalls or long sleeved shirt. (EN 1149-1)

Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged contact, use rubber or neoprene gloves. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Other skin protection

Materials for protective clothing:

Appropriate footwear and any additional skin protection measures must be selected on the basis of the task being performed and the risks involved, and must be approved by an expert before using this product.

8.2.2.3. Respiratory protection

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140) .

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Emissions from ventilation or processing equipment must be monitored to ensure they meet the requirements of environmental protection legislation. In some cases, scrubbers, filters or technical modifications of the process equipment are necessary to reduce the emissions to an acceptable level.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Different colours.
Odour	: Characteristic.
Odour threshold	: Not available
pH	: 6 – 7 (ISO 19396-1:2017)
Relative evaporation rate (butylacetate=1)	: Not available
Melting point	: 0 °C (Published data)
Freezing point	: 0 °C (Published data)
Boiling point	: 100 °C (Published data)
Flash point	: Not relevant/applicable due to nature of the product.
Auto-ignition temperature	: Not relevant/applicable due to nature of the product.
Decomposition temperature	: When exposed to heat, may decompose liberating hazardous gases
Flammability (solid, gas)	: Not flammable in the presence of the following materials or conditions: open fire, sparks and static discharge, heat and shock and mechanical impact. Not highly flammable, but may catch fire if continuously exposed to flame or high temperature.
Vapour pressure	: Not relevant/applicable due to nature of the product.
Relative vapour density at 20 °C	: 1 (Published data)
Relative density	: Calculated value (ISO 2811-1:2016)
Density	: ≈ 1.49 g/cm ³ Calculated value (ISO 2811-1:2016)
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Pow)	: Not applicable
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Viscosity, kinematic	: 2349 mm ² /s
Viscosity, dynamic	: 125 – 130 KU (Krebs Stomer) @20°C
Explosive properties	: Not explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. No unusual hazard in case of fire.
Oxidising properties	: No data available.
Explosive limits	: No data available

9.2. Other information

No additional information available

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

Strong bases. Strong oxidizers. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Combustion generates: Toxic gases. Carbon oxides (CO, CO₂). fume.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
LD50 oral	1020 mg/kg bodyweight
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l

Kaolin, calcined (92704-41-1)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat	> 2.19 mg/l

Skin corrosion/irritation : Not classified
pH: 6 – 7 (ISO 19396-1:2017)

Additional information : Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin

Serious eye damage/irritation : Not classified
pH: 6 – 7 (ISO 19396-1:2017)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SPS Isomat plus	
Viscosity, kinematic	2349 mm ² /s

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Potential adverse human health effects and symptoms : This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The mixture has been assessed following the conventional method of the Regulation (EC) No. 1272/2008 [CLP] and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See Heading 3.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
LC50 - Fish [1]	2.18 mg/l
EC50 - Crustacea [1]	2.94 mg/l
EC50 - Other aquatic organisms [1]	2.94 mg/l waterflea
EC50 - Other aquatic organisms [2]	0.11 mg/l
EC50 72h - Algae [1]	0.11 mg/l
ErC50 algae	0.11 mg/l [Selenastrum capricornutum, 72h]
NOEC (chronic)	1.2 mg/l
NOEC chronic fish	0.21 mg/l
NOEC chronic crustacea	1.7 mg/l
NOEC chronic algae	0.04 mg/l

Kaolin, calcined (92704-41-1)	
LC50 - Fish [1]	> 1000 mg/l (Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 700 mg/l
ErC50 algae	> 1000 mg/l

12.2. Persistence and degradability

SPS Isomat plus	
Persistence and degradability	There are no data available on the preparation itself. This product has not been tested for biodegradation.

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
Biodegradation	> 80 %

12.3. Bioaccumulative potential

SPS Isomat plus	
Partition coefficient n-octanol/water (Log Pow)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	Not applicable
Bioaccumulative potential	There are no data available on the preparation itself.

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
BCF - Fish [1]	6.95 (OECD 305)

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

Partition coefficient n-octanol/water (Log Pow)	0.7
Partition coefficient n-octanol/water (Log Kow)	0.7 (OECD 117)

12.4. Mobility in soil

SPS Isomat plus

Ecology - soil : There are no data available on the preparation itself.

12.5. Results of PBT and vPvB assessment

SPS Isomat plus

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Additional information : Product may not flow into sewer or superficial water

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Do not allow to enter drains or water courses.
Waste treatment methods : The generation of waste should always be avoided or kept to a minimum wherever possible. Disposal of this product, solutions and any by-products should always be in accordance with the applicable environmental protection and waste disposal legislation and any other regional or local regulations. Have surplus and non-recyclable products disposed of by a licensed disposal company. Do not dispose of untreated waste through the sewer unless in full compliance with the requirements of the competent authorities.
Product/Packaging disposal recommendations : Dispose of this material and its container in a safe way. Use caution when handling empty containers/containers that have not been cleaned or rinsed. Empty containers or inner bag may contain some residual product. Avoid dispersal of spilt material and waste material and prevent contact with soil, waterways, drains and sewers.
European List of Waste (LoW) code : 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 12 - waste paint and varnish other than those mentioned in 08 01 11
08 01 15* - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Special transport precautions : Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code : Not determined.
Ship type : Not determined.
Pollution category : Not determined.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : This product is not covered by the Seveso Directive.

—

SPS Isomat plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products:

EU limit value for SPS Isomat plus (cat. A/g): 30 g/l.

SPS Isomat plus Contains max 5.00 g/l VOC.

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
2	Hazards identification	Added	
3.2	Composition/information on ingredients	Modified	
8	Control parameters	Modified	
9	Physical and chemical properties	Added	
11	Toxicological information	Modified	
12.	Ecological information	Modified	
15	Seveso	Added	

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
EUH208	EUH208	Calculation method
EUH211	EUH211	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.