

## Technical datasheet

# HEAT RESISTANT spray paint 400 ml

Heat resistant (up to 650°C.), fast drying matt black spray paint for exhausts, barbecues, stove pipes and other metals exposed to heat. Cover the area of the surface to be sprayed. For interior and exterior use.

### Substrate:

The surface must be clean, dry and free of grease. Remove any rust and flaking paint layers first before sanding. Mask off the surrounding area. Do not apply a primer.

### Handling:

Before use, shake the spray can vigorously for at least 1 minute, during which time the mixing ball can be heard (also shake occasionally during use). Spray a sample first. Apply in 2 to 3 thin layers at a distance of approx. 20-30 cm. Curing is achieved after 60 minutes at 200°C. Take into account the development of smoke during this process and ensure good ventilation! After use, reverse the spray can and spray the paint residue out of the valve. Application temperature: min. 15°C. Consumption: Approx. 1-2 m<sup>2</sup> per 400 ml.

**Drying time (at 23°C and relative humidity of 65%):** Apply each next coat within 10 minutes. Agitate the spray can before applying the next coat. Allow the paint to dry for one hour at room temperature and subsequently heat for 60 minutes at 200°C to cure the paint coating. The drying time depends on the ambient temperature, the relative humidity and the coating thickness.

### General:

- It is better to apply several thin layers, instead of one thick layer.
- Work in a well ventilated area. If necessary, use appropriate safety equipment.
- Do not use at temperatures below 10°C., when it is likely to rain, frost is expected, or in direct sunlight.
- Store in a dry, cool and frost-free place.

### Technical data

<b>Content</b>	400 ml
<b>Colour</b>	Black
<b>Heat resistance</b>	Up to 650°C
<b>General</b>	Do not use at temperatures below 10°C. Do not use outside when it is likely to rain, frost is expected, or in direct sunlight. The spray can must be kept at room temperature (minimum of 15°C). Never place the spray can on a heat source.
<b>Storage</b>	Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.
<b>Surplus product</b>	This paint and the packaging should be disposed of at a collection point for hazardous or special waste.
<b>Hazard classification</b>	See MSDS

The effectiveness of our systems is based on developments in the raw material suppliers' materials and our practical experience. We cannot, however, be held liable without qualification for the work produced based on those systems, as the final result will be determined, in part, by the state of the substrates and other factors that are outside of our control. The current publication makes previously published technical sheets null and void.