

Description: Colourless, water-based transparent primer based on synthetic resin dispersion. For interior use in dry rooms only.

Use: For priming porous substrates. Counteracts the excessive porosity of the substrate. Ensures excellent adhesion on the substrate and increases coverage when finishing with a latex top coat.

Properties:

- Good penetration
- Virtually odourless
- Quick drying

Colour: Milky white, but colourless when dry.

Application: Shake well before use. Do not dilute, apply in one coat using a woolly roller or square pasting brush. If a film begins to form within 10 seconds after application (glossy patches), remove them immediately with a dry cloth. Caution: do not use Finess Transparent Primer on non-absorbent substrates! Water test: sprinkle some water on the surface. If the water is absorbed immediately (i.e. if the water does not drip off), the surface is porous.

Covers: Approx. 6-10 m²/litre per coat, strongly dependent on substrate porosity.

Drying time at 23°C and relative humidity of 65%:

Dry after approximately 2 hours.

Finish when completely cured after approx. 6 hours

SYSTEM CONSTRUCTION

Substrate: Must be solid, smooth, clean and dry and must be free from dust or grease. Repair cracks and fissures. Remove and repair any loose and unstable coats. Suitable substrates include plaster, plasterboard, gypsum blocks, bricks, etc.

In the case of a decorative plaster finish: Only use on new white render and stucco. Always use Finess Plaster Pre-treatment for all other substrates.

In the case of a latex top coat: Use on new or non-primed render and stucco, plasterboard, bricks, etc.

TECHNICAL DATA

Binding agent: Synthetic resin dispersion

Solvent: Water

Solid components: 10% in volume

Sp. Gr.: Approx. 1 g/ml

Viscosity: 20 sec Din cup 4 @ +20°C

Degree of gloss: Glossy

Tint: Colourless after drying

Dilute with: Do not dilute.

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Water and soap

Performance: Makes paint easier to apply and improves efficiency of subsequent coats.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: Do not use at temperatures below +8°C. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.