

**Description:** Good filler, moisture-controlling alkyd primer. For interior and exterior use.

**Application:** For wood, board, primed metal and plasterwork.

**Properties:**

- Good filler
- Excellent hiding power
- Moisture-controlling
- Easy to sand
- Even coverage

**Handling:** Stir well before use. Apply 1 or 2 coats inside, 2 coats outside with a brush, varnish roller or paint sprayer. Lightly sand, make it free of dust and fill, if necessary, in-between layers. Sand and reprime filled surfaces.

**Covers:** Approx. 13-16 m<sup>2</sup> per litre per coat depending on the object to be painted and the application method.

**Drying time at 23°C and relative humidity of 65%:**

Dust-dry after approx. 2 hours.

Can be painted over after approx. 18 hours.

SYSTEM CONSTRUCTION

**Substrate:** The surface must be clean, dry and free from dust or grease. Slightly round off the sharp corners to obtain good edge coverage.

**Unprimed wood:** Degrease, sand lightly and remove any dust.

**Metal:** Degrease, remove all rust and make free of dust. Treat with antirust red oxide primer and, next, apply an intermediate coat of Finess Primer.

**Plasterwork:** Degrease, sand lightly and remove any dust.

TECHNICAL DATA

**Binding agent:** Modified glycerophthalic resins

**Pigments:** Rutile titanium dioxide and mineral extenders

**Solvent:** White spirit

**Solid components:** 62% volume

**SG:** Approx. 1.4 g/ml

**Viscosity:** ICI Rotothinner 8-9 Poise @ +20°C

**Fineness:** <35 micron

**Recommended coat thickness:** 35 microns dry

**Degree of gloss:** Matt

**Tint:** White and grey

**Dilute with:** Do not dilute.

**Flash point:** Approx. 39°C

**Hazard classification:** See safety information sheet (MSDS)

**Tool cleaning instructions:** White spirit or brush cleaner.

**Performance:** Has a shelf life of a few months after opening and can be applied to wood that contains maximum 20% moisture.

**Storage:** Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

**General:** Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. Do not apply in direct sunlight or when it is likely to rain. After use, close the container correctly, turn it upside down for a few seconds to prevent skin formation and then store in an upright position.

**Surplus product:** This paint and the packaging should be disposed of at a collection point for hazardous or special waste.