

Description: Quick drying, moisture-controlling filling primer. For interior and exterior use.

Application: For wood, board, primed metal and plasterwork.

Properties:

- Quick drying
- Good filler
- Excellent hiding power
- Moisture-controlling
- Easy to sand
- Even coverage

Handling: Stir well before use. Apply 1 or 2 coats inside, 2 coats outside with a brush, varnish roller or paint sprayer. Lightly sand, make it free of dust and fill, if necessary, in-between layers. Sand and reprime filled surfaces.

Covers: Approx. 16 m²/litre per coat depending on the object to be painted and the application method.

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 1 hours.
Can be painted over after approx. 5 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Slightly round off the sharp corners to obtain good edge coverage.

Unprimed wood: Degrease, sand lightly and remove any dust.

Metal: Degrease, remove all rust and make free of dust. Treat with a suitable anti-rust Finess primer, then Finess Quick Primer.

Plasterwork: Degrease, sand lightly and remove any dust.

TECHNICAL DATA

Binding agent: Modified glycerophthalic resins

Pigments: Rutile titanium dioxide and mineral extenders

Solvent: White spirit

Solid components: 65% by volume

SG: Approx. 1.65 g/ml

Viscosity: ICI Rotothinner 7 Poise @ +20°C

Fineness: 6 using Hegman gauge

Recommended coat thickness: 35 microns (dry)

Degree of gloss: Matt

Tint: White

Flash point: Approx. 39°C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or brush cleaner.

Performance: Has a shelf life of a few months after opening and can be applied to wood that contains maximum 20% moisture. Can even be recoated on the same day.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: We recommend applying at +8°C and 30°C. Do not apply outdoors direct sun or when it is likely to rain. Close the container correctly, rotate to ensure that skin forming cannot occur and store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.