

Description: A water-based, exterior opaque wood stain that protects and finishes exterior timber. It can be used on all softwoods, especially on finely sawn timber panelling. Its weather-resistant, water-repellent satin finish resists flaking, peeling and cracking. Very easy to maintain, it can be recoated without sanding.

Use: Suitable for external use such as wooden wall cladding, fascias, doors, window frames etc.

Properties:

- Water-based
- Moisture-regulating
- Weather-resistant
- Economical to apply
- Very easy to apply
- Satin gloss

Covers: Approx. 12 m²/litre per coat depending on the object to be painted and the application method.

Directions for use

Stir thoroughly prior to use. Only dilute with 5% water if applying with a spray gun.

Apply in 2 or 3 coats in the direction of the grain using a suitable flat/round brush.

Preparation

The surface must be clean and free of dust and grease. Carefully remove green algae and moss.

Unprimed wood:

Degrease using water and ammonia (use thinner for merbau and meranti), slightly break sharp edges, sand lightly in the direction of the grain and remove any dust residue.

Treated wood in good condition: Degrease, sand lightly in the direction of the grain and wipe off any dust residue.

Treated wood in poor condition: Remove old coats using paint stripper, by scraping or sanding and prepare in the same way as unprimed wood.

TECHNICAL DATA

Binding agent: Acrylic dispersion

Pigments: Colour pigments

Solvent: Water

Solid components: 24 % volume

Sp. Gr.: Approx. 1.05 g/ml

Granule size: 15 microns

Recommended layer thickness: 35 microns (dry)

Degree of gloss: Satin gloss

Tint: Black

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Use water and soap.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: We recommend applying at temperatures between +8°C and +30°C. Do not apply in direct sunlight or when it is likely to rain. After use, close the container correctly and store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.