

COLOURLESS WALL VARNISH

Description: Water repellent, protective and colourless varnish based on an acrylic resin dispersion. Designed to make decorative plasters, concrete, brick and cement, etc. more weather resistant and/or easier to clean. For interior and exterior use.

Application: Designed to make decorative plasters, concrete, brick and cement, etc. more weather resistant and/or easier to clean.

Properties:

- Colourless protective coating
- Easy to clean
- Weather and alkali resistant
- Water repellent

Colours: Colourless.

Handling:

Stir well before use. Do not dilute! Apply with a brush, roller or sprayer. Outside: Apply a thin layer to make decorative plaster more weather resistant. Inside: apply 1 or 2 layers to make decorative plaster more washable. Apply 1 thin layer to remove dust from brick or cement.

Covers: Approx. 5-10 m² per litre per layer depending on the object to be painted and the application method.

Drying time at 23°C and relative humidity of 65%:

Dry after approximately 2 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be firm, clean, dry and free from dust or grease. Sand and repair surface irregularities. Remove and restore any loose and unstable coats. If using externally, first, remove all moss, mould and algal growth.

New decorative plasterwork:

Leave to harden for a minimum of 14 days.

Existing plasterwork:

Wash with water and a degreasant and allow to dry.



COLOURLESS WALL VARNISH

TECHNICAL DATA

Binding agent:	Pure acrylate
Pigments:	N/A
Solvent:	Water
Solid components:	30 v/v %
S.M.:	Approximately 1.02 g/ml
Viscosity:	50 Sec. din/cup 4 @ 20°C
Recommended coat thickness:	1 layer
Degree of gloss:	Glossy
Tint:	Colourless
Dilute with:	Do not dilute.
Hazard classification:	See MSDS
Tool cleaning instructions:	Use water and soap.

Performance: Makes undercoats more washable and more weather resistant.

Storage: Minimum 12 months in tightly closed original packing in a dry, cool and frost-free place.

General: Do not apply in temperatures below +8°C., in direct sun or when rain is possible. Allow newly cemented surfaces to set for at least 6 weeks. Ventilate during and after use.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.