

Description: Ready-to-use, colourless pre-treatment primer based on a synthetic resin dispersion. Should be applied to highly absorbent substrates such as new stucco or plasterwork before applying a decorative plaster. Good film-forming properties, odour-free and quick drying. If smooth plasterwork is painted with wall paint, the substrate must be pre-treated with SPS Fixator stabilising primer. For interior use in dry rooms.

Use: As a transparent primer on highly and/or irregularly absorbent but stable mineral substrates. Suitable surfaces include: cement and plasterwork, brick, gypsum panelling, etc. Do not use in wet rooms.

Properties:

- Reduces substrate suction
- Ready for immediate use
- Quick drying
- Good adhesion
- Virtually odourless

Colour: Milky white, but colourless when dry.

Application:

Stir thoroughly prior to use. Apply evenly in 1 coat using a square pasting brush or a woolly roller. Never allow this product to form a film.

Covers: approx. 10 -15 m²/litre per coat The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

Drying time at 23°C and relative humidity of 65%:

Dry after approximately 2 hours.

Recoat/plaster after approximately 6 hours.

SYSTEM CONSTRUCTION

General:

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Repair cracks and surface irregularities. Remove and/or repair all loose and unstable coats.

New, untreated substrates

- Prime highly absorbent surfaces in their entirety using SPS Transparent primer (prevent glossy patches).

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

Note: Only use on highly absorbent substrates!

(Test the surface by sprinkling some water against the wall. If the water is sucked immediately into the wall, the surface is absorbent. If the water runs down the wall, the surface is not absorbent.)

TECHNICAL DATA (applies to transparent/colourless)

Binding agent:	Synthetic resin dispersion
Solvent:	Water
Solid components:	7.5 v/v %
Specific mass:	Approximately 1.00 g/ml
Recommended coat thickness:	Do not apply excessively or allow a film to form. Immediately remove glossy patches with water and a cloth or a sponge.
Dilute with:	Do not dilute.
Hazard classification:	See MSDS
Tool cleaning instructions:	Use water and soap.

Shelf life: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General:

Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain, when frost is expected or in direct sunlight. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

Surplus product: This product and the packaging should be disposed of at a collection point for hazardous or special waste.