

Description: Colourless, extra matt, water-based, non-yellowing varnish. Makes painted walls easier to clean and walls painted in a dark colour more resistant to white marks. Darker tints appear more intense in colour. Quick-drying and solvent-free. For interior use.

Use: As an extra protective layer on walls that have already been painted with wall paint. Suitable surfaces include: existing coats of paint, cement and plasterwork, concrete, brick, glass fibre fabric, etc.

Properties:

- Extra matt
- Colourless
- Prevents white marks after cleaning
- Does not yellow
- Even coverage
- Low-odour and quick drying

Colour: Colourless. The use of SPS Wall varnish can give darker substrate colours greater intensity/greater depth.

Application: Stir well before use. Do not dilute. Apply in 1 or 2 coats using a suitable brush or paint roller. Always work wet-on-wet to prevent visible marks in the paint. Back-roll all overlaps in the same direction. Do not touch up when drying.

Covers: 16 - 20 m²/litre per coat. The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

Drying time at 23°C and relative humidity of 65%:

Dry after approximately 1 hour.

Can be painted over after approximately 4 hours.

Variations in coating thickness, temperature, humidity etc. affect the drying time.

SYSTEM CONSTRUCTION

General:

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

Existing intact coats of wall paint

- Clean using SPS Paint cleaner.
- Allow to dry before painting with Wall varnish mat.

The system described above applies for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA (applies to colourless/transparent)

Binding agent:	Alkyd emulsion
Pigments:	Transparent
Solvent:	Water
Solid components:	28% v/v
Specific mass:	Approximately 1.05 g/ml
Recommended coat thickness:	Dry coating thickness/coat: 35 micrometres Wet coating thickness/coat: 125 micrometres
Degree of gloss:	extra matt, 5% @ 85°
Dilute with:	Do not dilute.
Hazard classification:	See MSDS
Tool cleaning instructions:	Use water and soap.

Shelf life: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: The values stated in this technical data sheet have been determined based on DIN EN 13300. Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.