

**Description:** Colourless, glossy, water-based, non-yellowing varnish. Makes painted walls easier to clean and walls painted in a dark colour more resistant to white marks. Darker colours appear more intensive in colour. Quick-drying and solvent-free. For interior use.

**Use:** As an extra protective layer on walls that have already been painted with wall paint. Suitable surfaces include: existing coats of wall paint, cement and plasterwork, concrete, brick, glass fibre fabric, etc.

**Properties:**

- Glossy
- Colourless
- Prevents white marks after cleaning
- Does not yellow
- Even coverage
- Low-odour and quick drying

**Colour:** Colourless. The use of SPS Wall varnish gloss can give darker substrate colours greater intensity/greater depth.

**Application:** Stir well before use. Do not dilute. Apply in 1 or 2 coats using a suitable brush or paint roller. Always work wet-on-wet to prevent visible marks in the paint. Back-roll all overlaps in the same direction. Do not touch up when drying.

**Covers:** 16 - 20 m<sup>2</sup>/litre per coat. The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

**Drying time at 23°C and relative humidity of 65%:**

Dry after approximately 1 hour.

Can be painted over after approximately 4 hours.

Variations in coating thickness, temperature, humidity etc. affect the drying time.

### SYSTEM CONSTRUCTION

**General:**

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

**Existing intact coats of wall paint**

- Clean using SPS Paint cleaner.
- Allow to dry before painting with Wall varnish gloss

The system described above applies for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA (applies to colourless/transparent)

<b>Binding agent:</b>	acrylic dispersion
<b>Pigments:</b>	Transparent
<b>Solvent:</b>	Water
<b>Solid components:</b>	26% v/v
<b>Specific mass:</b>	Approximately 1.02 g/ml
<b>Recommended coat thickness:</b>	Dry coating thickness/coat: 35 micrometres Wet coating thickness/coat: 135 micrometres
<b>Degree of gloss:</b>	Satin gloss, 60% @ 60°
<b>Dilute with:</b>	Do not dilute.
<b>Hazard classification:</b>	See MSDS
<b>Tool cleaning instructions:</b>	Use water and soap.

**Shelf life:** Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

**General:** The values stated in this technical data sheet have been determined based on DIN EN 13300. Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

**Surplus product:** This paint and the packaging should be disposed of at a collection point for hazardous or special waste.