

Description: Highly opaque matt and highly washable wall paint based on synthetic resin dispersion. For indoor use.

Application: Especially suited for painting indoor walls and ceilings in living rooms, bedrooms, hallways etc. Do not use this product in bathrooms or kitchens. Suitable substrates are: cement and plasterwork, concrete, brickwork, plasterboard, board, wallpaper, etc. Also suitable for painting glass fibre fabric.

Properties:

- Covers in one coat
- Good washability
- Easy to apply

Colours: Available in white. This product can also be tinted with universal colorants.

Handling: Stir thoroughly prior to use. Apply in 1 or 2 coats with a square pasting brush, woolly roller or airless spray. Dilute the first layer with no more than 5% of water as required. Apply the second layer undiluted.

Covers: According to ISO-6504-3 and DIN EN 13300 approx. 10 m²/litre per coat, depending on the surface. Deposition efficiency: class 3

Drying time at 23°C and relative humidity of 65%:
Dust-dry after approx. 2 hours.
Can be painted over after approx. 5 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

New plasterwork: Prime with Finess Wall Paint Primer or Finess Primer Transparent.

Existing plasterwork: Clean using water and a degreasing agent. Allow to dry. Prime with Finess Wall paint Primer or Finess Primer Transparent.

Powdery substrates: Clean thoroughly with clean water and allow to dry. Prime with Finess Stabilising Primer.

Non water-resistant (rub-resistant) coats of paint:
Wash thoroughly until the surface does not flake or dust anymore. Next, prime with Finess Stabilising Primer..

Concrete: Remove any 'cement skin' and dust thoroughly using a brush. Allow to dry. Next prime the surface with Finess Wall Paint Primer. After Drying, finish with Finess Wall paint Ultra

Aerated (cellular) concrete blocks: Prime using a special priming agent. Next, apply a coat of plaster. After drying, prime the surface with Finess Wall Paint Primer.

Plasterboard: Bridge the joints with plaster mesh tape and fill with a suitable filler. After allowing to dry: Next prime the surface with Finess Wall Paint Primer..

MDF, chipboard and fibreboard: Sand smooth boards, remove any dust and seal the surface using Finess Sealing Primer.

Load-bearing coats of paint: Clean using water and a degreasing agent. First, sand down glossy coats of paint until matt and carefully ensure the substrate is free of dust.

Substrates stained by nicotine, damp, rust or soot:
Wash with water and a degreasing agent and allow to dry well. Next, seal the surface of the substrate with Finess Sealing Primer.

TECHNICAL DATA

Binding agent: Solvent-free vinyl bases copolymer-dispersion

Pigments: Rutile titanium dioxide and mineral fillers

Solvent: Water

Solid components: 43% by weight

SG: Approx. 1.45 g/ml

Viscosity: Viscolab LC 3: 5.5 PaS @ 20°C

Fineness: 50 microns

Gloss level: Matt ISO-2813 and DIN EN 13300: 5-10% @85°

Tint: white

Dilute with: Water

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: Use water and soap.

Features: Wet Scrub resistance according to ISO-11998 and DIN EN 13300: class 2

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General:
Stir thoroughly prior to use. Do not apply in temperatures below +8°C, in direct sunlight or when rain is expected. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product:
This paint and the packaging should be disposed of at a collection point for hazardous or special waste.