



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 1 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1****Producer**

S.P.S. BV
Zilverenberg 16
5234 GM 's-Hertogenbosch. Nederland
Tel. +31 73 642 27 10
Fax. +31 73 642 60 95
e-Mail: info@spsbv.com
www.spsbv.com

Emergency Phone Nr. : +31 73 642 27 10
[7:30 - 16:30]

Responsible for distribution

S.P.S. BV
Zilverenberg 16
5234 GM 's-Hertogenbosch. Nederland
Tel. +31 73 642 27 10
Fax. +31 73 642 60 95
e-Mail: info@spsbv.com
www.spsbv.com

Emergency telephone (24h): +31 30 274 88 88
NL - Nationaal Vergiftigingen Informatie Centrum (NVIC)
[Only for doctors to inform accidental poisoning]

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name **SPS Metallic lak universeel - spuitlak.**

Type of product : Paint aerosol.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial and decoration painting / Paint aerosol.

1.3. Details of the supplier of the safety data sheet

Company identification : See producer or distributor.

1.4. Emergency telephone number

Phone nr : See producer or distributor.

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture****Classification EC 67/548 or EC 1999/45**

F+; R12
Xn; R20/21
R66
Xi; R36
R52-53

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Not yet regulated. (2015)

2.2. Label elements**Labelling EC 67/548 or EC 1999/45**

Symbol(s)



: Harmful.
Extremely flammable.

R Phrase(s)

: R12 : Extremely flammable.
R20/21 : Harmful by inhalation and in contact with skin.
R36 : Irritating to eyes.
R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66 : Repeated exposure may cause skin dryness or cracking.

S Phrase(s)

: S23 : Do not breathe spray.
S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S.P.S. BV

Zilverenberg 16 5234 GM 's-Hertogenbosch. Nederland



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 2 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1****SECTION 2. Hazards identification (continued)**

S29/56 : Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
 S36/37 : Wear suitable protective clothing and gloves.
 S46 : If swallowed seek medical advice immediately and show this container or label.
 S51 : Use only in well-ventilated areas.

Labelling Regulation EC 1272/2008 (CLP)

• Pictograms (Precautionary statements) : Not yet regulated. (2015)

Further Phrases

: Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – No smoking. Keep out of reach of children.

Contains : Xylenes. [EC No 215-535-7]

[For professionals, a safety data sheet is available on demand.]

2.3. Other hazards

Other hazards : Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis.
 Warning! Pressurized container.

SECTION 3. Composition/information on ingredients

3.1.1/3.2. Substance / Preparation : This product is defined as a mixture.

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or assigned an occupational exposure limit.

Substance name	Value(s)	CAS nr	EINECS nr	EC index	REACH	CERTIFICATE
Acetone	: 25 - 50 %	67-64-1	200-662-2	606-001-00-8	01-2119471330-49	F; R11 R66 R67 Xi; R36 ----- Undefined. (GHS)
	TGG 8 uur (nl) (mg/m ³) : 1210 (2420 (TGG 15 min.))					
Propane	: 12.5 - 20 %	74-98-6	200-827-9	601-003-00-5	01-2119486944-21	F+; R12 ----- Flam. Gas 1;H220 Compressed gas;H280
	TGG 8 uur (nl) (mg/m ³) : 1800					
Xylene	: 10 - 12.5 %	1330-20-7	215-535-7	601-022-00-9	01-2119488216-32	R10 Xn; R20/21 Xi; R38 ----- Flam. Liq. 3;H226 Acute Tox. 4 (Dermal);H312 Acute Tox. 4 (Inhalation);H332 Skin Irrit. 2;H315
	ILV (EU) - 8 H - [mg/m ³] : (221 Skin.) ILV (EU) - 8 H - [ppm] : (50 Skin.) ILV (EU) - 15 min - [mg/m ³] : (442 Skin.) ILV (EU) - 15 min - [ppm] : (100 Skin.)					
Butane	: 10 - 12.5 %	106-97-8	203-448-7	601-004-00-0	01-2119474691-32	F+; R12 ----- Flam. Gas 1;H220 Compressed gas;H280

S.P.S. BV

Zilverenberg 16 5234 GM 's-Hertogenbosch. Nederland



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 3 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak

AKP04419-1

SECTION 3. Composition/information on ingredients (continued)

TGG 8 uur (nl) (mg/m³) : 2400 (by supplier)

Substance name	Value(s)	CAS nr	EINECS nr	EC index	REACH	CERTIFICATE
Isobutane	10 - 12.5 %	75-28-5	200-857-2	601-004-00-0	01-2119485395-27	F+; R12 Flam. Gas 1;H220 Compressed gas;H280

TGG 8 uur (nl) (mg/m³) : Not established.

Ethylbenzene	5 - 10 %	100-41-4	202-849-4	601-023-00-4	01-2119489370-35	F; R11 Xn; R20 Flam. Liq. 2;H225 Acute Tox. 4 (Inhalation);H332
--------------	----------	----------	-----------	--------------	------------------	--

TGG 8 uur (nl) (mg/m³) : 215 (430 (TGG 15 min. H))

1,2,4-trimethylbenzene	2.5 - 5 %	95-63-6	202-436-9	601-043-00-3	01-2119472135-42	R10 Xn; R20 Xi; R36/37/38 N; R51-53 Flam. Liq. 3;H226 Acute Tox. 4 (Inhalation);H332 Eye Irrit. 2;H319 Skin Irrit. 2;H315 STOT SE3;H335 Aquatic Chronic 2;H411
------------------------	-----------	---------	-----------	--------------	------------------	---

TGG 8 uur (nl) (mg/m³) : 100 (NL 2007, 200 (TGG 15 min.))

Hydrocarbon-solvents (Aromatic)	2.5 - 5 %	64742-95-6	265-199-0	649-356-00-4	01-2119486773-24	R10 Xn; R65 R66 R67 Xi; R37 N; R51-53 Undefined. (GHS)
---------------------------------	-----------	------------	-----------	--------------	------------------	--

MAC [mg/m³] : 100

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	1 - 2.5 %	64742-48-9	919-857-5	649-327-00-6	01-2119463258-33	R10 Xn; R65 R66 R67 Asp. Tox. 1;H304 Flam. Liq. 3;H226 Not CLP (STOT SE 3; H336) EUH066
--	-----------	------------	-----------	--------------	------------------	--

TGG 8 uur (nl) (mg/m³) : 1200 (1200 mg/m³: CEFIC-HSPA)
(116 mg/m³: Recommendation in CLH-document - 2010)

Mesitylene	0.1 - 1 %	108-67-8	203-604-4	601-025-00-5	01-2119463878-19	R10 Xi; R37 N; R51-53 Flam. Liq. 3;H226 STOT SE3;H335 Aquatic Chronic 2;H411
------------	-----------	----------	-----------	--------------	------------------	---

TGG 8 uur (nl) (mg/m³) : Not applicable. (NL < 2007, 100)

Cumene	0.1 - 1 %	98-82-8	202-704-5	601-024-00-X	01-2119473983-24	R10 Xn; R65 Xi; R37 N; R51-53 Undefined. (GHS)
--------	-----------	---------	-----------	--------------	------------------	--

ILV (EU) - 8 H - [mg/m³] : (100 Skin.)

ILV (EU) - 8 H - [ppm] : (20 Skin.)

ILV (EU) - 15 min - [mg/m³] : (250 Skin.)

ILV (EU) - 15 min - [ppm] : (50 Skin.)

Propylbenzene	0.1 - 1 %	103-65-1	203-132-9	601-024-00-X	----	R10 Xn; R65 Xi; R37 N; R51-53 Undefined. (GHS)
---------------	-----------	----------	-----------	--------------	------	--

TGG 8 uur (nl) (mg/m³) : No data available.

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation : Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.
- Skin contact : Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

S.P.S. BV

Zilverenberg 16 5234 GM 's-Hertogenbosch. Nederland



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 4 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak

AKP04419-1

SECTION 4. First aid measures (continued)

- Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- Ingestion : If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. Drink large quantities of water.

4.2. Most important symptoms and effects, both acute and delayed

No information is on file to date regarding acute and/or delayed post-exposure symptoms and effects.

4.3. Indication of any immediate medical attention and special treatment needed

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
If unconscious place in recovery position and seek medical advice.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Extinguishing media

- Suitable : Dry chemical. Alcohol resistant foam. Carbon dioxide. Water fog.
- Not to be used



Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

Incomplete combustion will generate poisonous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

Flammable class : Extremely flammable.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : No smoking. Equip cleanup crew with proper protection.

Technical measures : Eliminate every possible source of ignition.
Ventilate area.
Do not breathe vapours.
Refer to protective measures listed in sections 7 and 8

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 5 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1**

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Due to the organic solvents' content of the preparation:

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be:

- stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.

or

- laid out flat in a single layer to dry.

or

- placed in a closed metal container soaked with water.

or

- washed out well with warm soapy water before disposal.

Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Store in accordance with local/national regulations.

Notes on joint storage:

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Additional information on storage conditions:

Observe label precautions. Store between 5 and 30°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

SECTION 8. Exposure controls/personal protection

Engineering Measures : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

8.1. Control parameters

TLV-TWA [mg/m³] : See Heading 3 (Information on ingredients).



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 6 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1**

SECTION 8. Exposure controls/personal protection (continued)

8.2 Exposure controls

Personal protection



- Respiratory protection : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.
- Skin protection : Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.
- Eye protection : Use safety eyewear designed to protect against splash of liquids.
- Hand protection : For prolonged contact, use nitrile or neoprene gloves or other material resistant to petroleum oils.
Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1.a. Appearance

- Physical state : Aerosol (contains Liquefied gas)
Colour : Silver.

9.1.b. Odour

- Odour : Characteristic. (White Spirit)

9.1.c. Odour threshold

- Odour threshold : Not determined.

9.1.d. pH

- pH value : Not determined.

9.1.e. Melting point / Freezing point

- Freezing point [°C] : No data available.
Melting point [°C] : Not determined.

9.1.f. Initial boiling point - boiling range

- Initial boiling point [°C] : Not usable. (aerosol)
Final boiling point [°C]

9.1.g. Flash point

- Flash point [°C] : < 0 , Not usable. (aerosol)

9.1.h. Evaporation rate

- Evaporation rate (ether=1) : No data available.

9.1.i. Flammability

- Flammability : Extremely flammable aerosol

9.1.j. Explosion limits (lower - upper)

- Explosion limits : When mixed with air and exposed to ignition source, can burn in open air or explode if confined.
Explosion limits - lower [%] : 1.1
Explosion limits - upper [%] : 13.0



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 7 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1**

SECTION 9. Physical and chemical properties (continued)

9.1.k. Vapour pressure

Vapour pressure [hPa] : 30000 (22502 mm Hg) (@ 20 °C)

9.1.l. Vapour density

9.1.m. Relative density

Density [kg/m³] : 706

9.1.n. Solubility

Solubility in water : Insoluble.

9.1.o. Partition coefficient : n-octanol / water

Log P octanol / water at 20°C : No data available.

9.1.p. Auto-ignition temperature

Auto-ignition temperature [°C] : 365 (The product does not ignites spontaneously.)

9.1.q. Thermal decomposition

Thermal decomposition : There are no data available on the preparation itself. When exposed to heat, may decompose liberating hazardous gases. (See Heading 10. SDS)

9.1.r. Viscosity

Viscosity : Not determined.

9.1.s. Explosive Properties

Explosive Properties : Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

9.1.t. Oxidising properties

Oxidising properties : No data available.

9.2. Other information

SECTION 10. Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

See Heading 7.

10.6. Hazardous decomposition products

Such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11. Toxicological information

On product

: There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous mixtures Directive 1999/45/EC and classified for toxicological hazards accordingly. See MSDS Sections 2 and 15 for details.



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 8 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1**

SECTION 11. Toxicological information (continued)

11.1. Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

On ingredients

Substance list :	Rat inhalation LC50 [mg/m ³ /4h]	Rabbit dermal LD50 [mg/kg]	Rat oral LD50 [mg/kg]
Acetone [EC No 200-662-2]	39	20000	5800
Xylene [EC No 215-535-7]	22.1	2000	4300
Butane [EC No 203-448-7]	658	----	----
Ethylbenzene [EC No 202-849-4]	----	17800	3500
1,2,4-trimethylbenzene	----	----	5000
Hydrocarbon-solvents (Aromatic)	>15	>3000	>5000
Naphtha, hydrotreated heavy	>2.8	>3000	>15000

SECTION 12. Ecological information

12.1. Toxicity

On product : The mixture has been assessed following the conventional method of the Dangerous mixtures Directive 1999/45/EC and is classified as dangerous for the environment. See Sections 2 and 3 for details.

On ingredients

48 H-LC50 - Daphnia magna [mg/l] : Acetone [EC No 200-662-2] : 2262
48 H-CE50 - Daphnia magna [mg/l] : Acetone [EC No 200-662-2] : 39
Xylene [EC No 215-535-7] : 7.4
Hydrocarbon-solvents (Aromatic)
[EC No 265-199-0] : 7.4 (24 hrs.: 150 mg/l)
LC50-96 Hour - fish [mg/l] : Acetone [EC No 200-662-2] : 5540
Xylene [EC No 215-535-7] : 13.5
Hydrocarbon-solvents (Aromatic)
[EC No 265-199-0] : 3.77
Naphtha, hydrotreated heavy
[EC No 265-150-3] : >100

12.2. Persistence and degradability

Persistence and degradability : No data available. May cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential

Bioaccumulative potential : No data available.

12.4. Mobility in soil

Not determined. If the product contaminates lakes, rivers or sewers, inform appropriate authorities in accordance with local regulations.



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 9 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1**

SECTION 12. Ecological information (continued)

12.5. Results of PBT and vPvB assessment

This product is not, or does not contain, a substance that is a PBT or a vPvB.

12.6. Other adverse effects

Ecological effects information : -

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Prevent entry to sewers and public waters. May pollute public waters. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Disposal : Do not allow into drains or water courses.

Dispose of this material and its container to hazardous or special waste collection point.

Industrial waste number : 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS.

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances.

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11.

15 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 04 Metallic packaging

Uncleaned packaging:

Recommendation: Not completely empty packaging must be treated complying Directive 91/689/EEC.

SECTION 14. Transport information

14.1. UN number

- UN No. : 1950

14.2. UN proper shipping name

- Proper shipping name : UN1950 AEROSOLS, 2.1, 5F, (D)

14.3. Transport hazard class(es)

Hazard Label(s)



: Extremely flammable.

- ADR/RID : Class : 2

- H.I. nr : --



MATERIAL SAFETY DATA SHEET (1907/2006/EC)

Page : 10 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak**AKP04419-1**

SECTION 14. Transport information (continued)

14.4. Packing group

- ADR Packing group : Group : F

14.5. Environmental hazards

14.6. Special precautions for user

General information

: Transport within user's premises:
Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in accordance with ADR/RID, IMDG and ICAO/IATA.

Emergency action in case of accident : Stop the engine. No naked lights. No smoking. Mark roads and warns other road users. Keep public away from danger area.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ensure all national/local regulations are observed.

Contains : Xylenes. [EC No 215-535-7]

Other



: - Packaging with an tactile warning of danger.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

VOC-EU limit

: (Cat. A/..) Not applicable.
g/l (2010): Not applicable.
This product contains max. VOC g/l: 706,0
This product contains max. VOC (%): 93,3

15.2. Chemical safety assessment

A Chemical Safety Assessment is not executed.

SECTION 16. Other information

Text of R-Phrases in § 3

: R10 : Flammable.
R11 : Highly flammable.
R12 : Extremely flammable.
R20 : Harmful by inhalation.
R20/21 : Harmful by inhalation and in contact with skin.
R36 : Irritating to eyes.
R36/37/38 : Irritating to eyes, respiratory system and skin.
R37 : Irritating to respiratory system.
R38 : Irritating to skin.
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 : Harmful : may cause lung damage if swallowed.
R66 : Repeated exposure may cause skin dryness or cracking.



**MATERIAL SAFETY DATA SHEET
(1907/2006/EC)**

Page : 11 / 11

Revision nr : 1

Date : 4 / 7 / 2011

Supersedes : 4 / 7 / 2011

SPS Metallic lak universeel - spuitlak

AKP04419-1

SECTION 16. Other information (continued)

Further information R67 : Vapours may cause drowsiness and dizziness.
: None.

The contents and format of this MSDS are in accordance with EEC Commission Directive 1907/2006/EC.

DISCLAIMER OF LIABILITY The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document