



Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin) [UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 3-8-2016 Revision date: 3-8-2016 Supersedes: 27-9-2013 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)
[UNOFFICIAL DOCUMENT]
Product code : 65166060101
Product group : Woodstain - Vernish

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer uses, Professional use, Industrial use
Use of the substance/mixture : Industrial and decoration painting

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

S.P.S. BV
Zilverenberg 16
5234 GM 's-Hertogenbosch. - Nederland.
T +31 (0)73 642 27 10 - F +31 (0)73 642 60 95
info@spsbv.com - www.spsbv.com

Responsible formatting SDS

Mantech Nederland B.V.
Kobaltweg 7
5234 GN 's-Hertogenbosch - Nederland
T +31 (0)73 70 70 112 - F +31 (0)73 64 43 861
info@mantechbv.nl - www.mantechbv.nl

1.4. Emergency telephone number

Emergency number : SPS BV.: +31 73 642 27 10 [7:30 - 16:30]

NL - Nationaal Vergiftigingen Informatie Centrum (NVIC)
Emergency telephone (24 hours): +31 30 274 88 88
(Only for doctors to inform accidental poisoning)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Warning
Hazardous ingredients : Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics
Hazard statements (CLP) : H226 - Flammable liquid and vapour
H336 - May cause drowsiness or dizziness

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Precautionary statements (CLP)	: H412 - Harmful to aquatic life with long lasting effects P102 - Keep out of reach of children P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves, protective clothing, eye protection P312 - Call a POISON CENTER or doctor/physician if you feel unwell P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation [Spray application; P261 - Avoid breathing spay.]
EUH-statements	: EUH208 - Contains 2-butanone oxime(96-29-7)(202-496-6). May produce an allergic reaction EUH066 - Repeated exposure may cause skin dryness or cracking EUH210 - Safety data sheet available on request
Security closing plug for children	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics	(EC no) 919-446-0 (REACH-no) 01-2119458049-33	10 - 25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-48-9 (EC no) 919-857-5 (REACH-no) 01-2119463258-33	10 - 25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Talc substance with national workplace exposure limit(s) (NL)	(CAS No) 14807-96-6	10 - 25	Not classified
2-ethylhexanoic acid, zirconium salt	(CAS No) 22464-99-9 (EC no) 245-018-1 (REACH-no) 01-2119979088-21	< 1	Repr. 2, H361
2-butanone oxime	(CAS No) 96-29-7 (EC no) 202-496-6 (EC index no) 616-014-00-0 (REACH-no) 01-2119539477-28	< 1	Carc. 2, H351 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317

Specific concentration limits:

Name	Product identifier	Specific concentration limits
2-ethylhexanoic acid, zirconium salt	(CAS No) 22464-99-9 (EC no) 245-018-1 (REACH-no) 01-2119979088-21	(C >= 3) Repr. 2, H361

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
First-aid measures after inhalation	: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.
First-aid measures after skin contact	: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

- First-aid measures after eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- First-aid measures after ingestion : If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : No information is on file to date regarding acute and/or delayed post-exposure symptoms and effects.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : carbon dioxide (CO₂), powder, alcohol-resistant foam, water spray.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

5.3. Advice for firefighters

- Precautionary measures fire : Cool closed containers exposed to fire with water.
- Other information : Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Use personal protective equipment as required.
- Emergency procedures : Do not smoke. Avoid ignition sources. Ventilate area. Do not breathe vapours.

6.1.2. For emergency responders

- Protective equipment : Equip rescue crew with proper protection.
- Emergency procedures : No smoking. Avoid ignition sources. Ventilate area. Do not breathe vapours.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
- Other information : Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Due to the organic solvents' content of the preparation: Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

- Precautions for safe handling : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding. For personal protection see Section 8. Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be:
- stored in purpose-built containers or in metal containers with tight-fitting self-closing lids or
 - laid out flat in a single layer to dry or
 - placed in a closed metal container soaked with water or
 - washed out well with warm soapy water before disposal.
- Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
- Hygiene measures : Smoking, eating and drinking should be prohibited in application area.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed and dry.
- Storage conditions : Observe the label precautions. Store in accordance with local/national regulations.
- Storage temperature : 5 - 30 °C Store in dry, well-ventilated area.
- Heat and ignition sources : Keep away from heat and direct sunlight.
- Prohibitions on mixed storage : Store separately from oxidising agents and strongly alkaline and strongly acidic materials.
- Storage area : Prevent unauthorised access.
- Special rules on packaging : Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment:

Protective goggles. Gloves. In case of inadequate ventilation wear respiratory protection.

Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged contact, use rubber or neoprene gloves. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred

Eye protection:

Use safety eyewear designed to protect against splash of liquids

Skin and body protection:

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Every part of the skin which had contact with the product should have been washed thoroughly

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Different colours.
Odour	: Characteristic. (solvents).
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 100 - 220 °C [ASTM D-86; information White Spirit supplier]
Flash point	: 41 (≥ 30) °C [ASTM D-56; information White Spirit supplier]
Auto-ignition temperature	: No data available
Decomposition temperature	: When exposed to heat, may decompose liberating hazardous gases
Flammability (solid, gas)	: This product is flammable
Vapour pressure	: < 5 hPa at 20 °C
Relative vapour density at 20 °C	: (lucht = 1): > 1 @ 101 kPa [betreffende water] [berekend] [information White Spirit supplier]
Relative density	: No data available
Density	: 955 - 1005 kg/m ³
Solubility	: Water: Negligible.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 220 - 250 cP [ICI Rotothinner, 20 °C]
Explosive properties	: No dangerous reactions known.
Oxidising properties	: No data available.
Explosive limits	: 0,6 - 8 vol %

9.2. Other information

VOC content : (cat.A/e): 400 g/l (2010). This product contains max. 400 g/l VOC.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

See Heading 7.

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

10.6. Hazardous decomposition products

Such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : There are no data available on the preparation itself. Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008. See Sections 2 and 3 for details

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 4 ml/kg
LC50 inhalation rat (mg/l)	> 13,1 mg/l [4 hrs.]
2-butanone oxime (96-29-7)	
LD50 oral rat	> 2326 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	> 1000 mg/kg
LC50 inhalation rat (mg/l)	0,02 mg/l/4h
2-ethylhexanoic acid, zirconium salt (22464-99-9)	
LD50 oral rat	> 5 g/kg
LD50 dermal rabbit	> 5 g/kg

Skin corrosion/irritation : Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin
pH: Not applicable

Serious eye damage/irritation : The liquid splashed in the eyes may cause irritation and reversible damage
pH: Not applicable

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The mixture has been assessed following the conventional method of the Regulation (EC) No. 1272/2008 [CLP] and is classified as dangerous for the environment. See Sections 2 and 3 for details.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
LC50 fish 1	> 1000 mg/l [96 h.]
EC50 Daphnia 1	> 1000 mg/l [48 h.]
ErC50 (algae)	> 1000 mg/l pseudokirchneriella subcapitata, 72 h.
NOEC (chronic)	0,23 mg/l [72 h.]
NOEC chronic fish	0,131 mg/l
2-butanone oxime (96-29-7)	
LC50 fish 1	> 100 mg/l 96 h., Lepomis macrochirus
LC50 fish 2	693 mg/l 96 h., Oncorhynchus mykiss

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

2-butanone oxime (96-29-7)	
EC50 Daphnia 1	> 500 mg/l 48 h.
EC50 Daphnia 2	750 mg/l
ErC50 (algae)	83 mg/l 72 h., Scenedesmus subspicatus

12.2. Persistence and degradability

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin) [UNOFFICIAL DOCUMENT]

Persistence and degradability: There are no data available on the preparation itself. May cause long-term adverse effects in the aquatic environment.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

Biodegradation: > 80 % 28 days, OECD 301B, OECD 301F

12.3. Bioaccumulative potential

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin) [UNOFFICIAL DOCUMENT]

Log Pow: No data available
Log Kow: No data available
Bioaccumulative potential: There are no data available on the preparation itself.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

Log Pow: 5 - 6,5

2-butanone oxime (96-29-7)

Log Pow: 0,59 - 0,63

12.4. Mobility in soil

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin) [UNOFFICIAL DOCUMENT]

Ecology - soil: There are no data available on the preparation itself.

12.5. Results of PBT and vPvB assessment

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin) [UNOFFICIAL DOCUMENT]

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Additional information: Product may not flow into sewer or superficial water

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste): Do not allow to enter drains or water courses.
Waste disposal recommendations: Dispose of this material and its container to hazardous or special waste collection point.
Additional information: Uncleaned packaging: Recommendation: Not completely empty packaging must be treated complying Directive 91/689/EEC.
European List of Waste (LoW) code: 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN






ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1263	1263	1263	1263	1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III	UN 1263 PAINT, 3, III	UN 1263 PAINT, 3, III

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Special transport precautions : Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage

- Overland transport

Transport regulations (ADR) : This preparation requires, in a package <450 liter, the conditions from Annex A of the ADR under 2.2.3.1.5, and is therefore not subject to the rules of the ADR.

Classification code (ADR) : F1

Special provisions (ADR) : 163, 640E, 650

Limited quantities (ADR) : 5l

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1

Mixed packing provisions (ADR) : MP19


Tank code (ADR) : LGBF

Vehicle for tank carriage : FL

Transport category (ADR) : 3

Hazard identification number (Kemler No.) : 30

Orange plates :



Tunnel restriction code (ADR) : D/E

EAC code : •3YE

- Transport by sea

Special provisions (IMDG) : 163, 223, 955

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

Special packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T2

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-E

Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1

PCA Limited quantities (IATA) : Y344

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72
ERG code (IATA)	: 3L

- Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 64E, 65
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

- Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 640E, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

IBC code	: Not determined.
Ship type	: Not determined.
Pollution category	: Not determined.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

VOC content : (cat.A/e): 400 g/l (2010). This product contains max. 400 g/l VOC.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Finess Beits UV transparant zijdeglans (Woodstain UV transparent satin)

[UNOFFICIAL DOCUMENT]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Indication of changes:

1.1	Product code	Modified
-----	--------------	----------

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking
EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request

SDS EU (REACH bijlage II) [NIET VOOR UITGIFTE]

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product