

**Description:** High coverage and easy to wash down wall paint. Breathable and low-odour. For finishing exterior walls and walls and ceilings in damp areas such as kitchens and bathrooms. For interior and exterior use.

**Application:** Applicable anywhere indoors and for exterior use particularly suited to façades, concrete fences etc. Suitable substrates include: Cement and plasterwork, concrete, brick, plasterboard, board, wallpaper etc.

**Properties:**

- Scrub-resistant
- Matt
- Durable
- Easy to apply
- Moisture-controlling

**Colours:** White, can be tinted by using universal tinting pastes if required.

**Handling:** Stir thoroughly prior to use. Dilute the first coat with no more than 10% of water if required. Apply the second coat undiluted. Apply with a brush, woolly roller or airless spray.

**Covers:** According to ISO-6504-3 and DIN EN13300 approx. 8m<sup>2</sup>/litre per coat, depending on the surface. Deposition efficiency: class 3

**Drying time at 23°C and relative humidity of 65%:**  
Dry: after approx. 2 hours.  
Can be painted over after approx. 6 hours.

#### SYSTEM CONSTRUCTION

**Substrate:** The surface must be clean, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. First, remove all moss, mould and algal growth when using outdoors.

**New plasterwork:** Prime with Finess Wall paint Primer Interior/Exterior or FinessTransparent Primer (interior use).

**Existing plasterwork:** Clean using water and a degreasing agent. Allow to dry. Prime with Finess Wall paint Primer Interior/Exterior.

**Powdery substrates:** Clean thoroughly with clean water and allow to dry. Prime with Finess Stabilising Primer.

**Non water-resistant (rub-resistant) coats of paint:** Wash thoroughly until the surface does not flake or dust anymore. Next, prime with Finess Stabilising Primer.

**Concrete:** Remove any 'cement skin' and dust thoroughly using a brush. Next, prime the surface with Finess Wall paint Primer Interior/Exterior.

**Plasterboard:** Bridge the joints with plaster mesh tape and fill with a suitable filler. After allowing to dry: prime the surface with Finess Wall Paint Primer.

**MDF, chipboard and fibreboard:** Sand smooth boards, remove any dust and seal the surface using Finess Sealing Primer.

**Load-bearing coats of paint:** Clean using water and a degreasing agent. First, sand down glossy coats of paint until matt and carefully ensure the substrate is free of dust.

**Substrates stained by nicotine, damp, rust or soot:** Wash with water and a degreasing agent and allow to dry well. Next, seal the surface of the substrate with Finess Sealing Primer.

#### TECHNICAL DATA

**Binding agent:** Synthetic resin dispersion

**Pigments:** Rutile titanium dioxide and mineral fillers

**Solvent:** Water

**Solid components:** 63% by weight

**SG:** Approx. 1.55 g/ml

**Viscosity:** Viscolab LC 3: 5.5 PaS @ 20°C

**Fineness:** 50 microns; ISO-787-7 and DIN EN 13300 fine

**Degree of gloss:** Medium gloss ISO-2813 and DIN EN 13300: 60°/2.3% 85°/13%

**Tint:** White

**Dilute with:** Water

**Hazard classification:** See safety information sheet (MSDS)

**Tool cleaning instructions:** Use water and soap.

**Features:** Washability according to DIN 53778: >5000 cycles. Class S Scrub-resistance to ISO-11998 and DIN EN 13300: Class 3

**Storage:** Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

**General:** Stir thoroughly prior to use. Do not apply at temperatures below +8°C, in direct sunlight or when rain is expected. Allow newly cemented surfaces to set for at least 6 weeks.

**Surplus product:** This paint and the packaging should be disposed of at a collection point for hazardous or special waste.