

Description: Farmer's Green protects exterior woodwork very effectively and gives it an attractive appearance as the dark green colour accentuates the wood grain. Can be applied to both fresh unprimed wood and impregnated wood. Farmer's Green penetrates deeply into the wood, has a moisture-regulating effect and does not flake. For outdoor use.

Application: Stir thoroughly prior to use. Apply using a flat/round brush (use a paint roller after application to distribute the paint evenly on large surfaces). For maximum penetration, dilute the first coat on unprimed wood with a maximum of 5% turpentine/white spirit, do not dilute the second and third coat. Lightly sand and remove any dust between the coats. Apply 3 coats on unprimed wood and 2 coats when carrying out maintenance.

Covers: Approx. 12 m²/litre per coat, depending on the surface.

Drying time at 23°C and relative humidity of 65%:

Dust dry after approximately 4 hours.
Can be painted over after approximately 18 hours.

SYSTEM CONSTRUCTION

Substrate: Must be solid, clean, dry and free from dust and grease. Badly adhering non-transparent coats of stain must be scraped off or sanded back to bare wood and repaired with a wood filler if required.

Preparation

Unprimed wood: degrease using water and ammonia (use thinner for merbau and meranti), slightly break sharp edges, sand lightly and remove any dust.

Painted surface in good condition: degrease, sand lightly and remove any dust.

Painted surfaces in poor condition: remove using paint stripper, using a torch, or by scraping and prepare in the same way as unprimed wood.

Old coats of acrylic paint (water-soluble): remove and treat as unprimed wood.

TECHNICAL DATA

Binding agent: Glycerophthalic resins

Pigments: Colour pigments

Solvent: White spirit

Solid components: 40% in volume

Sp. Gr.: Approx. 1.03 g/ml

Viscosity: ICI Rotothinner 6-7 Poise @ +20°C

Granule size: 15 microns

Recommended coat thickness: 3 x 35 microns (dry), at a coverage of 12 m²/litre

Degree of gloss: Gloss. 60-70% with Gardner 60° gloss meter

Tint: FARMER'S GREEN

Dilute with: White spirit

Flash point: 39°C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or brush cleaner

Performance: Microporous: moisture-permeable, allows the wood to breathe.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General information: Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. Do not apply in direct sunlight or when it is likely to rain. After use, close the container correctly, turn it around for a few seconds to ensure that skin formation cannot occur and store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.