

Description:

Ferrous wall paint for interior use only.
Attracts magnets.

Use:

After treatment magnets will stick to the painted surface. Can be used to create a magnetic memo board on a wall. Can be finished with any wall paint. Suitable substrates are: cement and plasterwork, concrete, brickwork, plasterboard, board, wallpaper, etc.

Properties:

- Solvent-free and virtually odourless
- Ferrous acrylic wallpaint
- Matt

Colour:

Dark grey

Application:

Stir well before use. Do not dilute. Apply in at least 3 coats for a magnet attracting surface with a brush or roller.

Spreading rate:

According to ISO-6504-3 and DIN EN 13300 approx. 5 m²/l, depending on the substrate. To obtain a maximal magnetic effect, we recommend at least 3 coats (min. ±1.000 µm dry). Spreading rate for 3 covers: approx. 1,7 m²/l.

Drying time at 23°C and rel. humidity 65%:

Dust-dry: After approx. 2 hours. Recoatable: After approx. 4-6 hours.

SYSTEM

SYSTEM CONSTRUCTION

New plasterwork: Prime with Finess Wall Paint Primer or Finess Transparent .

Existing plasterwork: Clean using water and a degreasing agent. Allow to dry. Prime with Finess Wall paint Primer.

Powdery substrates: Clean thoroughly with clean water and allow to dry. Prime with Finess Stabilising Primer.

Non water-resistant (rub-resistant) coats of paint:

Wash thoroughly until the surface does not flake or dust anymore. Next, prime with Finess Stabilising Primer.

Concrete: Remove any 'cement skin' and dust thoroughly using a brush. Next prime the surface with Finess Wall Paint Primer.

Aerated (cellular) concrete blocks: Prime using a special priming agent. Next, apply a coat of plaster. After drying, prime the surface with Finess Wall Paint Primer.

Plasterboard: Bridge the joints with plaster mesh tape and fill with a suitable filler. After allowing to dry: Next prime the surface with Finess Wall Paint Primer..

MDF, chipboard and fibreboard: Sand smooth boards, remove any dust and seal the surface using Finess Sealing Primer.

Load-bearing coats of paint: Clean using water and a degreasing agent. First, sand down glossy coats of paint until matt and carefully ensure the substrate is free of dust.

Substrates stained by nicotine, damp, rust or soot:

Wash with water and a degreasing agent and allow to dry well. Next, seal the surface of the substrate with Finess Sealing Primer.

Wallpapering of magnetic wall paint:

Paint the wall according the directions. After at least 24 hours: sand gently and wallpaper with thin paper.

TECHNICAL DATA

Binding agent: Acrylic resin dispersion

Pigments: Rutile titanium dioxide and ferrous fillers

Solvent: Water

Solid components: 55% in volume

S.G.: Approx. 2,65

Gloss degree: Mat

Dilution: Water

Hazard classification:

Please refer to MSDS.

Cleaning instructions:

Clean tools with water and soap.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Do not use at temperatures below +8°C. Allow newly cemented surfaces to set for at least 6 weeks.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.