

Description: Good filler, moisture-controlling alkyd primer. For interior use.

Application: For wood, board, primed metal and plasterwork.

Properties:

- Good filler
- Excellent hiding power
- Moisture-controlling
- Easy to sand
- Even coverage

Handling: Stir well before use. Apply 1 or 2 coats with a brush, varnish roller or paint sprayer. Lightly sand in-between coats, remove any dust and fill if required. Sand and reprime filled surfaces.

Covers: Approx. 14-16 m² per litre per coat depending on the object to be painted and the application method.

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 2 hours.

Can be painted over after approx. 18 hours.

SYSTEM CONSTRUCTION

Substrate: The surface must be clean, dry and free from dust or grease. Slightly round off the sharp corners to obtain good edge coverage.

Unprimed wood: Degrease, sand lightly and remove any dust.

Metal: Degrease, remove all rust and make free of dust. Treat with antirust red oxide primer and, next, apply an intermediate coat of Finess Primer Promo.

Plasterwork: Degrease, sand lightly and remove any dust.

TECHNICAL DATA

Binding agent: Modified glycerophthalic resins

Pigments: Rutile titanium dioxide and mineral extenders

Solvent: White spirit

Solid components: 51% volume

SG: Approx. 1.4 g/ml

Viscosity: ICI Rotothinner 9-10 Poise @ +20°C

Fineness: <30 microns

Recommended coat thickness: 35 microns dry

Degree of gloss: Matt

Tint: White

Dilute with: Do not dilute.

Flash point: Approx. 39°C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or brush cleaner.

Performance: Has a shelf life of a few months after opening and can be applied to wood that contains maximum 20% moisture.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Stir thoroughly prior to use. We recommend applying at 8°C and 30°C. After use, close the container correctly, turn it around for a few seconds to ensure that skin formation cannot occur and store in an upright position. Do not close doors and windows until the paint has dried fully (after a minimum of 8 hours).

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.