

Description: High gloss finishing coat for wood, hard plastics and metal, with excellent hiding power. For interior use.

Application: On wood and pre-treated metal/plastic. Can also be applied as top coat for plasterwork.

Properties:

- Excellent hiding capacity
- Durable
- Good flow
- Easy to maintain

Colours: White and various colours

Handling: Stir thoroughly prior to use. Apply with a brush, roller or paint sprayer. Apply in 1 or 2 coats. After every coat, lightly sand down and remove dust.

Covers: Approx. 14 m²/litre per coat.

Drying time at 23°C and relative humidity of 65%:

Dust-dry after approx. 3 hours.

Can be painted over after approx. 20 hours.

SYSTEM CONSTRUCTION

Substrate: Surfaces must be clean, dry and free from dust or grease.

Unprimed wood: Degrease, sand lightly and remove any dust. Next, apply Finess Primer. Allow to dry. Next sand the surface, remove dust and fill any irregularities if present. Apply primer to filled areas

Painted surfaces in good condition: Carefully degrease with a degreasing agent, sand down lightly and remove dust. If necessary, fill irregularities with filler and apply Finess Primer. Sand to a smooth finish.

Painted surfaces in poor condition: Remove all poorly adhering paint using paint stripper or a blowtorch/hot air paint removal gun. Then treat as "Unprimed wood".

Untreated MDF, chipboard, etc.: Degrease, sand lightly and remove any dust. Next, apply Finess Primer. Allow to dry. Next sand the surface, remove dust and fill any irregularities if present. Next, apply a second coat of Finess Primer.

Untreated metal: Carefully remove grease, any mill scale and rust. Pre-treat with a suitable Finess rust preventive primer. Next, apply a coat of Finess Primer.

Hard plastics: Degrease, lightly sand and remove any dust. Prime with 1 coat of Finess Multi Primer

Plasterwork: Surfaces must be completely dry and free from dust or grease. Next, apply 1 coat of Finess Primer..

TECHNICAL DATA

Binding agent: Glycerophtalic resins

Pigments: Rutile titanium dioxide (white) and/or colouring agents

Solvent: White spirit

Solid components: 56% in weight, depending on colour

SG: Approx. 1.16 g/ml, depending on colour

Viscosity: ICI Rotothinner 7-9 Poise @ +20°C

Recommended coat thickness: 30 microns per coat dry

Finess: <10 microns

Degree of gloss: Minimum of 85% with Gardner 60°C gloss meter

Tint: White and various colours

Flash point: 39°C

Hazard classification: See safety information sheet (MSDS)

Tool cleaning instructions: White spirit or paint cleaner.

Features: High resistance against chemical maintenance products. Perfect edge coverage. Adherence G.T.O.

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: We recommend applying with temperatures between +8°C and +30°C.

Products based on alkyd resins have a tendency to yellow in a dark environment or when covered. When exposed to daylight, this phenomenon is much reduced.

After use, close the container correctly, turn it around for a few seconds to ensure that skin formation cannot occur and store in an upright position.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.