

Description

Universal metallic paint, quick drying, excellent adhesive properties and suitable for use on substrates such as metal, concrete, wood, brick, etc. For the best results, only apply to carefully prepared surfaces.

Properties

- Quick drying
- Excellent adhesion
- Very high hiding capacity

Substrate:

The surface must be clean, dry and free of grease. Remove any rust and flaking paint layers first before sanding. In the case of exterior applications, remove all moss, mould and algal growth. Mask off the surrounding area.

Application

The surface must be clean, dry and free of grease. Allow the spray can to reach ambient temperature. The ideal application temperature is 15 to 25°C. Before use, agitate the spray can vigorously for 2 minutes and spray a test surface. Hold the spray nozzle at a distance of 25 to 30 centimetres from the surface to be sprayed.

Apply in 2 to 3 light coats. Apply the second and third coat when the previous coat is still wet, or wait until the previous coat has completely cured. Agitate the spray can again before applying each of the subsequent coats. After use, clean the spray nozzle (turn the spray can upside down and press the nozzle down for approximately 5 seconds).

Covers: 1 to 2 m² per coat, depending on the object to be painted and the application method.

Drying time at 23°C and relative humidity of 65%:

Dust-free: After 5 to 10 minutes

Tack-free: After 10 to 20 minutes

The drying time depends on the ambient temperature, the relative humidity and the coating thickness.



TECHNICAL DATA

Content:	500 ml
Base:	Acrylate
Colour:	Silver - aluminium
VOC content:	Approximately 93 m/m %
Solid components:	Approximately 7 m/m %
Heat resistance:	Up to 110°C
Hazard classification:	See MSDS

Storage: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Do not use at temperatures below 10°C. Do not use outside when it is likely to rain, frost is expected, or in direct sunlight. The spray can must be kept at room temperature (minimum of 15°C). Never place the spray can on a heat source.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.