

Description: Durable, decorative plaster with excellent adhesion and bark effect, based on a synthetic resin dispersion. Excellent application properties, breathable, resistant to impact and knocks. For interior use.

Use: Suitable surfaces include all smooth and even surfaces such as: concrete, brick, cement and plasterwork, existing coats of paint, gypsum panelling, board, fine float finish plaster, etc.

Properties:

- Durable
- Impact and knock resistant
- Easy to apply.
- Excellent adhesion
- Breathable
- Easy to paint over

Colour: White and in light colours in the SPC Color Service colour mixing system. For optimal coverage, use SPS Plaster pretreatment in a colour that matches the colour of the top coat.

Application:

Mix thoroughly prior to use.

If required, dilute with a maximum of 5% water.

Apply evenly using a stainless steel plastering trowel with a thickness that matches the grain. Next, using a plastic plastering trowel, texture the plaster with a circular motion to create a smooth, evenly grainy surface. Texturing using a plastic plastering trowel in a vertical motion creates a tree bark effect.

Covers:

2 mm Medium: approx. 2.5 kg/m²

3 mm Coarse: approx. 3 kg/m²

The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.

Drying time at 23°C and relative humidity of 65%:

Dry after approximately 6 hours.

Cures after a few days.

Variations in temperature, humidity etc. affect the drying time.

System structure

General:

The surface must be smooth and even, capable of supporting the plaster, completely set, clean, dry, and free of dust or grease. Repair cracks and surface irregularities. Remove and/or repair all loose and unstable coats.

Before applying SPS Decorative plaster, first prime using SPS Plaster pretreatment.

New, untreated substrates

- Plasterboard boards: Mask seams with plaster tape and seal using a suitable filler.
- Concrete: Thoroughly remove any cement skin and fill any holes. If a coat of plaster is applied to all of the concrete first, prime the concrete using SPS Concrete primer before the coat of plaster is applied.
- Cellular concrete and sand-lime bricks: Clean, prime using SPS Concrete impregnation and level out using gypsum plaster.
- Gypsum plasterwork: Carefully remove dust.
- Thoroughly clean powdery surfaces. Prime using Fixator after allowing to dry.

Existing, load-bearing substrates:

- Clean surface.
- Make surface/textured surface smooth and even.

Existing, non-load-bearing substrates

- Thoroughly remove loose coats.
- Thoroughly wash powdery coats and allow them to dry.
- Carry out any repairs.
- Prime with SPS Fixator.
- Make surface/textured surface smooth and even.

Contamination caused by nicotine, damp, rust or soot

- Clean thoroughly.
- Treat surface/stain with SPS Sealing primer.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

TECHNICAL DATA (apply to the colour white)

Binding agent:	Synthetic resin dispersion
Pigments:	Rutile titanium dioxide, fillers and round quartz grains
Solvent:	Water
Solid components:	71 % v/v
Specific mass:	Approximately 2.0 g/ml
Recommended coat thickness:	Apply each layer to the grain thickness.
Degree of gloss:	Matt
Dilute with:	Water
Hazard classification:	See MSDS
Tool cleaning instructions:	Use water and soap.

Shelf life: Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

General: Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Always use the required personal protective equipment when applying this product. Do not inhale spray mist/fumes given off by products. Always ventilate appropriately when applying. There may be slight variations in colour since natural raw materials are used. Please therefore blend pots with a different batch number prior to use.

Surplus product: This product and the packaging should be disposed of at a collection point for hazardous or special waste.