

ROOF TILE RENOVATION PAINT

Description:

100 % high-quality roof renovation acrylic Provides long-term protection against harmful weather influences and acid rain.

Application:

Can be applied outside on weathered sloping roofs covered in concrete tiles, fibre cement slates or corrugated sheeting.

Properties:

- Slightly satin
- Permanently elastic
- Excellent adhesion
- Weather-resistant.
- Breathable
- Colourfast and UV resistant

Colour:

Black, red, brown, grey, blue-black, evening pink and orange.

Application:

Stir thoroughly prior to use. Always apply 2 coats with a brush, woolly roller or airless spray. Dilute the first coat with 10% water depending on substrate suction. *Do not dilute the second coat!*

Airless spray: (\pm 150 bar, nozzle opening 17) dilute the first coat with 20% water and apply the second coat undiluted once the first coat is dry. Always spray wet-on-wet.

Covers:

Approximately 2-2.5 m²/l, depending on the surface.

15 l = approximately 40 m² in two coats.

SYSTEM CONSTRUCTION

Substrate:

Check the substrate for irregularities and/or leaks. Remove all loose parts with a steel brush or scrape off with a filling knife. Next, clean thoroughly using a high-pressure cleaner or mechanically to ensure that all dirt, efflorescence, grease, dust, algae and moss has been removed. Then rinse thoroughly using clean water and allow to dry. Avoid the long time between the cleaning and application of the fibracryl (max. 3 weeks).

Application data:

- t°: Minimum object temperature 10°C
- Avoid temperatures that are too high (>30°C) to ensure that drying is not too quick and that blistering, dark patches or overlaps cannot occur.
- Do not apply when the atmospheric humidity (fog/mist) is high or when it might rain.

ROOF TILE RENOVATION PAINT

TECHNICAL DATA

Binding agent: 100% acrylic resin dispersion with high alkali resistance.

Pigments: Iron oxide and minerals and fillers.

Solvent: Water

PVC: Approximately 25%

S.M.: Approx. 1.25 g/ml \pm 0.1 (depending on the colour)

Viscosity: Brookfield RVT 30-35 PS @ +20°C

Fineness: 5 using Hegman gauge

Recommended layer thickness: 400-500 grammes per m² in 2 coats.

Degree of gloss: Eggshell

Dilute with: Water

Hazard classification: See MSDS

Cleaning instructions: Use water and soap

Performance: Excellent adherence and good colour fastness.

Storage: Minimum of 12 months in tightly closed original packing in a dry, cool and frost-free place.

General: Do not apply outdoors when it is likely to rain or when frost is expected. Do not apply outdoors in direct sun. When using this product, always use the necessary personal protective equipment. Do not inhale the spray or fumes from products. Always ventilate appropriately when applying.

Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.